



Identification	Part No.	Drawing	Dimensions in mm
Hybrid fibre optic cable, single mode, double ended 2 x FO + 3 x 2.5 mm ² , 2 x Han® 3 A Length: a = 1 m AC version DC version a = 5 m AC version DC version a = 10 m AC version DC version a = 20 m AC version DC version a = 40 m AC version DC version a = 50 m AC version DC version a = 100 m AC version DC version	33 57 211 0015 003 33 57 211 0015 004 33 57 211 0055 003 33 57 211 0055 004 33 57 211 0105 003 33 57 211 0105 004 33 57 211 0205 003 33 57 211 0205 004 33 57 211 0405 003 33 57 211 0405 004 33 57 211 0505 003 33 57 211 0505 004 33 57 211 1005 003 33 57 211 1005 004	double ended a = length Protection level: IP 65 / IP 67	
Hybrid fibre optic cable, single mode, single ended 2 x FO + 3 x 2.5 mm ² , 1 x Han® 3 A Length: a = 1 m AC version DC version a = 5 m AC version DC version a = 10 m AC version DC version a = 20 m AC version DC version a = 40 m AC version DC version a = 50 m AC version DC version a = 100 m AC version DC version	33 57 111 0015 003 33 57 111 0015 004 33 57 111 0055 003 33 57 111 0055 004 33 57 111 0105 003 33 57 111 0105 004 33 57 111 0205 003 33 57 111 0205 004 33 57 111 0405 003 33 57 111 0405 004 33 57 111 0505 003 33 57 111 0505 004 33 57 111 1005 003 33 57 111 1005 004	single ended a = length	
Hybrid fibre optic cable, single mode Length: 10 m Length: 20 m Length: 500 m	33 57 851 0100 003 33 57 851 0200 003 33 57 851 5000 003	 PVC jacket 2 x 9/125 + 3 x 2.5 mm ² Outer diameter: 8.8 mm Min. bending radius: Installation: 9 cm Operating: 18 cm	

Further cable lengths are available on request