


Equipment marking - LS-EMP-V4A (80X30) - 0803475

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Equipment marking, Stainless steel label, not polished, silver, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: snapped, lettering field size: 80 x 30 mm, Number of individual labels: 10



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	 4 055626 077918
GTIN	4055626077918
Weight per Piece (excluding packing)	144.000 g
Custom tariff number	73269098
Country of origin	Germany

Technical data

Dimensions

Length (b)	30 mm
Width (a)	80 mm

Ambient conditions

Ambient temperature (operation)	-80 °C ... 350 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color	silver
Components	free from silicone, halogen, and cadmium

Equipment marking - LS-EMP-V4A (80X30) - 0803475

Technical data

General

Material	V4A
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	10
Number of individual labels per row	2
Mounting type	snapped
Testing substances harmful to the wetting properties of lacquers (LABS conformity)	VDMA 24364-A1-L:2018-05
Result	Test passed
Result	Test passed
UV resistance	Following ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h
Temperature storage	IEC 60068-2-2:2007-07
Result	Test passed
Duration	240 h
Temperature for testing	350 °C
Temperature resistance	Following ANSI/UL 969-2018:03
Test duration	240 h
Rating 225 °C (250 °C)	Test passed
Test for wipe resistance of inscriptions	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Test duration	168 h
Test duration	168 h
Testing in a condensation changing climate in the presence of sulfur dioxide	following DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2
Salt spray test	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Classifications

eCl@ss

eCl@ss 10.0.1	27400629
eCl@ss 11.0	27281106
eCl@ss 5.0	27149100

Equipment marking - LS-EMP-V4A (80X30) - 0803475

Classifications

eCl@ss

eCl@ss 5.1	27141100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149129
eCl@ss 9.0	27400629

ETIM

ETIM 6.0	EC001288
ETIM 7.0	EC001530

UNSPSC

UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504

Accessories

Accessories

Magazine

Magazine - TOPMARK LASER-MAG SHEET - 0831836

Sheet magazine for TOPMARK LASER



Printing system accessories

Adapter plate - TMN-ADAPTER PLATE-LS - 1012104

Adapter plate, for LS materials, for TOPMARK NEO, weight: 0.193 kg

