


NOTES: UNLESS OTHERWISE SPECIFIED

1. P/N: X100WCOLOR
HOUSING & PLUNGER: MOLDED NYLON. AVAILABLE IN TEN COLORS.
CONTACT BLADE: GOLD PLATED BeCu.
SPRING: STAINLESS STEEL.
2. P/N: 9302COLOR
HOUSING: MOLDED NYLON. AVAILABLE IN ALL TEN COLORS.
FRAME: NICKEL PLATED BRASS.
CONTACT: NICKEL PLATED BeCu OR PHOSPHOR BRONZE.
HARDWARE: NATURAL NYLON NUT COVER. STAINLESS STEEL NUT.
BRASS EYELET. COPPER, TIN PLATED. TERMINAL RING.
3. P/N: W-600/COLOR
18AWG 65X36 TINNED COPPER
0.144 [3.66] O.D. PVC INSULATION
AVAILABLE IN TEN COLORS.
4. PERFORMANCE
MAXIMUM CURRENT: 4.0 AMPS
MAXIMUM VOLTAGE: 5000 W.V.D.C.
MAXIMUM TEMPERATURE: 221°F (105°C)

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED



		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ± ± .XXX ±		CONTRACT NO.		E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.	
				APPROVALS DATE			
				DRAWN R.L. 8/16		DESCRIPTION	
		MATERIAL SEE NOTE.		APPROVED BY		MINI-HOOK (X100W) TO SHRD R/A STD BAN PLUG (9302)	
		FINISH SEE NOTE.				SIZE CODE IDENT NO. DRAWING NO. REV.	
NEXT ASSY		USED ON				B 08505 633W	
APPLICATION		DO NOT SCALE DRAWING				SCALE 1:1 SHEET 1 OF 1	