



Main

Range of Product	Magelis XBT GC, GT/GK with control
Product or Component Type	CANopen bus master module
Product Compatibility	XBTGT2220 XBTGT2130 XBTGT2930 XBTGT2330 XBTGT5230 XBTGT6340 XBTGT4330 XBTGK5330 XBTGK2330 XBTGT2110 XBTGT5330 XBTGT5340 XBTGT5430 XBTGT7340 XBTGT4340 XBTGT2430 XBTGT2120 XBTGT6330 XBTGT4230 XBTGK2120
Integrated connection type	CANopen master bus male SUB-D 9, 2 twisted shielded pairs
Bus type	CANopen M10 DR 303-1 CANopen M10 DS 301 V4.02
Number of channels	64 RPDO 64 TPDO
[Us] rated supply voltage	5 V DC

Complementary

Transmission rate	100 kbit/s 1640.42 ft (500 m) 1000 kbit/s 164.04 ft (50 m) 125 kbit/s 1394.36 ft (425 m) 20 kbit/s 3280.84 ft (1000 m) 250 kbit/s 820.21 ft (250 m) 50 kbit/s 2624.67 ft (800 m) 500 kbit/s 410.10 ft (125 m)
Power dissipation in W	2.4 W 5 V DC
Number of modules per base controller	1
Number of slave	16
Supply	External supply
Marking	CE
Status LED	1 LED ERR 1 LED PWR 1 LED RUN
Net Weight	0.22 lb(US) (0.1 kg)

Environment

Product Certifications	UL
IP Degree of Protection	IP20
Ambient air temperature for operation	32...122 °F (0...50 °C)
Relative Humidity	10...90 % without condensation

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	22000 - Temporary Category for ITS Price Promotion
Discount Schedule	I
GTIN	3595864023793
Nbr. of units in pkg.	1
Package weight(Lbs)	10.41 oz (295 g)
Returnability	No
Country of origin	JP

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.56 in (6.5 cm)
Package 1 width	4.33 in (11 cm)
Package 1 Length	6.30 in (16 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Weight	15.10 lb(US) (6.847 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)

Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------


CANopen Bus Master Module for Advanced Panels

Dimensions



CANopen Bus Master Module for Advanced Panels

Mounting on an XBT GT/GK Panel



- (1) Magelis XBTGT or XBTGK
- (2) XBTZGCANM CANopen module