

# Continuous Flex

## SD 960 CY

Shielded continuous flex data cable for small bending radius



Marking for SD 960 CY 07852425:

SAB BRÖCKSKES · D-VIERSEN · 07852502 25 x 0.25 mm<sup>2</sup> SD 960 CY 24 AWG/25c 07852425 AWM Style 21083 80°C 300V CE

### Construction:

<b>Conductor:</b>	bare copper strands, extra fine wires
<b>Insulation:</b>	PVC, T12 acc. to EN 50363-3 + VDE 0207-363-3
<b>Color code:</b>	acc. to color code US 2, see page O/27
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Wrapping:</b>	non-woven tape
<b>Shielding:</b>	tinned copper braiding
<b>Wrapping:</b>	non-woven tape
<b>Jacket material:</b>	PVC, TM2 acc. to EN 50363-3 + VDE 0207-363-3
<b>Jacket color:</b>	black (RAL 9005)

### Outstanding features:



- good EMC characteristics
- very good flexibility
- small bending radius
- UV resistant jacket

### Technical data:

<b>Peak operating voltage:</b>	max. 350 V	
<b>Voltage UL:</b>	300 V	
<b>Testing voltage:</b>	conductor/conductor: 1500 V conductor/shielding: 1200 V	
<b>Min. bending radius:</b> <i>continuously flexing:</i>	7.5 x O.D.	
<b>Radiation resistance:</b>	8 x 10 <sup>7</sup> cJ/kg	
<b>Temperature range:</b> <i>static:</i> <i>flexing:</i>	DIN VDE -30/+70°C	UL/CSA: up to +80°C
<b>Burning characteristics:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, UL VW-1	
<b>Oil resistance:</b>	acc. to our internal standard, see page O/29	
<b>Approvals:</b>	UR AWM, CE, EAC, RoHS	
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page O/30	

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
<b>▶ 26 AWG (≈ 18/38) ▪ 0.14 mm<sup>2</sup></b>				
07852602	2	0.177	4.5	17
07852603	3	0.185	4.7	20
07852604	4	0.205	5.2	24
07852605	5	0.220	5.6	28
07852607	7	0.252	6.4	38
07852610	10	0.295	7.5	45
07852614	14	0.335	8.5	60
07852618	18	0.366	9.3	73
07852625	25	0.433	11.0	100

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
<b>▶ 24 AWG (≈ 32/38) ▪ 0.25 mm<sup>2</sup></b>				
07852402	2	0.193	4.9	20
07852403	3	0.205	5.2	24
07852404	4	0.217	5.5	28
07852405	5	0.244	6.2	36
07852407	7	0.280	7.1	43
07852410	10	0.335	8.5	60
07852414	14	0.362	9.2	75
07852418	18	0.398	10.1	92
07852425	25	0.492	12.5	134

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
<b>▶ 22 AWG (≈ 42/38) ▪ 0.34 mm<sup>2</sup></b>				
07852202	2	0.201	5.1	22
07852203	3	0.213	5.4	26
07852204	4	0.228	5.8	31
07852205	5	0.252	6.4	40
07852207	7	0.291	7.4	49
07852210	10	0.346	8.8	69
07852214	14	0.378	9.6	86
07852218	18	0.425	10.8	114
07852225	25	0.512	13.0	153

Other dimensions and colors are available on request

**Possible on request:**

- 20 AWG & 19 AWG
- with gray jacket and colored conductors with reference to DIN 47100