### Data sheet 17279.0 SQ 120/3





Cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 71 mm, Rated cross-section: 120 mm<sup>2</sup>, Colour: natural

### **Business data**

Article number	17279.0
Article name	SQ 120/3
GTIN (EAN)	4044211189358
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	97.88 g
Weight per piece (including packaging)	98.2 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Cross-connector
Colour	Natural

## Data sheet 17279.0 SQ 120/3



### **Technical data**

Dimensions	
Length	10 mm
Width	71 mm
Height	27.5 mm
Hole diameter	5.5 mm
Hole spacing (mid-point to mid-point)	27 mm
Pitch size	27 mm
Ratings	
Max. voltage	1000 V
Rated current	269 A
Current load, max.	290 A
Rated cross-section	120 mm <sup>2</sup>
Contamination degree	3
Connection data	
No. of poles	3
Screw head	Slotted
Screw threading	M 6
Tightening torque, min.	3.2 Nm
Tightening torque, max.	3.7 Nm
Materials	
Material	Copper
Surface	Tin-plated
Surface screw	Galvanized
Further technical data	
Mounting type	Screwable
Number of bridged terminals	3
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

## Data sheet 17279.0 SQ 120/3



### Media



# Data sheet 17279.0 SQ 120/3



#### Accessories

#### ##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 120 mm<sup>2</sup>, Width: 27 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17165.2	SRK 120/2A BG	4044211189372	5