



- NOTES:
1. MATERIAL: SEE BOM
 2. FINISHES: SEE BOM
 3. PRODUCT SPECIFICATION: NOT REQUIRED
 4. INCH DIMS ARE SHOWN IN PARENTHESIS (XXX)
 5. ALL CREEP DISTANCES FOR UL 1059, CLASS C, 600V GENERAL INDUSTRY
 6. FOR USE WITH #22-#12 AWG SOLID AND STRANDED WIRES
 7. TORQUE RATING: 5 IN-LB. MAX.
 8. PRODUCT PERFORMANCE SPECIFICATION PPS.95.001

6	9	SCREW	380010228	8704-0401-0220
5	9	CAGE CLAMP	380021494	8604-0101-A120
4	4	FRONT TERMINAL	380021593	9504-2101-R260
3	5	REAR TERMINAL	380021595	9504-2301-R260
2	1	BODY	399582016	9503-XX01 V000
1	1	CAP	399584116	9502-XX01 V000
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

EC NO. 3225
 DRWN: WH 07/14/03
 CH'K:
 APPR:

DESCRIPTION

REV

QUALITY SYMBOLS	MAJOR	CRITICAL	SPC
GENERAL TOLERANCES: (UNLESS SPECIFIED)	mm	INCH	
4 PLACES	±.0015	±.0015	
3 PLACES	±.038	±.005	
2 PLACES	±.13	±.01	
1 PLACE	±.3		
ANGULAR:	±2°		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			

SCALE 3:2	DESIGN UNITS	THIRD ANGLE PROJECTION
DRAWN BY & DATE	CHECKED BY & DATE	APPROVED BY & DATE
W. HOWARD 07/14/03		
CAD FILENAME	MATERIAL NO.	DRAWING NO.
95050910A-SP449	399590003	E-39959-003
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		

PROJECT NO. E-365

1	-
SHT	REV
REVISION	DATE
1	

REVISION ON CAD ONLY

TITLE: SR BTS PKT, #12 AWG, 9 ASY 600V, 20A, WITH IMPRINTING

MOLEX MOLEX INCORPORATED

SHEET NO. 1 OF 1

SIZE B