



Precision ESD Safe Dissipative Drivers

Wiha Precision ESD Static Dissipative Screwdrivers meet the requirements for tools used in static sensitive areas.



Rotating cap for precise turning & control with fingertip

Molded Precision handle of impact resistant dissipative material

Tapered handle allows rapid rotation

Blade, CVM steel, hardened, hard chrome finish

Tip, precision ground for exact fit, Wiha Chromtop finish

ESD Standard IEC 61340-5-1

Surface resistance of handles is 10⁶ - 10⁹ Ohms



272 **Slotted Screwdriver, With Precision ESD Safe Dissipative Handle.** Blade high alloy chrome-vanadium-molybdenum steel. Hard chrome finished. Handle manufactured from impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item No.	mm	Inch	mm	Inch	mm	Inch	mm	Inch	lbs.	pkg.
272 08	.8	1/32	40	1.6	0.16	.01	120	4.7	.02	10
272 10	1.0	.039	40	1.6	0.18	.01	120	4.7	.02	10
272 12	1.2	3/64	40	1.6	0.20	.01	120	4.7	.02	10
272 15	1.5	1/16	40	1.6	0.25	.01	120	4.7	.02	10
272 20	2.0	5/64	40	1.6	0.40	.02	120	4.7	.02	10
272 22	2.0	5/64	75	3.0	0.40	.02	155	6.1	.03	10
272 23	2.0	5/64	100	3.9	0.40	.02	180	7.1	.03	10
272 24	2.0	5/64	150	5.9	0.40	.02	260	10.2	.04	10
272 25	2.5	3/32	50	2.0	0.40	.02	145	5.7	.04	10
272 27	2.5	3/32	100	3.9	0.40	.02	195	7.7	.03	10
272 28	2.5	3/32	150	5.9	0.40	.02	245	9.6	.04	10
272 30	3.0	1/8	50	2.0	0.50	.02	145	5.7	.04	10
272 32	3.0	1/8	100	3.9	0.50	.02	210	8.3	.04	10
272 34	3.0	1/8	150	5.9	0.50	.02	260	10.2	.05	10
272 35	3.5	9/64	60	2.4	0.60	.02	170	6.7	.06	10
272 37	3.5	9/64	100	3.9	0.60	.02	210	8.3	.06	10
272 38	3.5	9/64	150	5.9	0.60	.02	260	10.2	.06	10
272 40	4.0	5/32	60	2.4	0.80	.03	170	6.7	.06	10
272 42	4.0	5/32	100	3.9	0.80	.03	210	8.3	.06	10
272 43	4.0	5/32	150	5.9	0.80	.03	260	10.2	.07	10

*Metric dimensions actual - Inch dimensions approximate



SHOP

272 90 **Set 8 Pcs. Slotted Precision ESD Safe Dissipative Handle**

Blade CVM steel, hardened, hard chromed. Handle impact resistant, dissipative material. In storage pouch. ESD standard IEC 61340-5-1

Item No.	mm	mm	mm	mm	lbs.	
272 90	272 08	.8	40	272 20	2.0 40	.54
	272 10	1.0	40	272 25	2.5 50	
	272 12	1.2	40	272 30	3.0 50	
	272 15	1.5	40	272 35	3.5 60	



SHOP

273 90 **Set 7 Pcs. Slotted & Phillips Precision ESD Safe Dissipative Handle.**

Blade high alloy CVM steel, hardened, hard chromed. Handle manufactured from impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item No.	mm	mm	Size	mm	lbs.	
273 90	272 15	1.5	40	273 05	00 40	.30
	272 20	2.0	40	273 10	0 50	
	272 25	2.5	50	273 20	1 60	
	272 35	3.5	60			