

## Screwdriver - SZK PH3 VDE - 1212536

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screwdriver, PH crosshead, VDE insulated, size: PH 3 x 150 mm, 2-component grip, with non-slip grip

The figure shows the SZK PH2 version

### Product Features

- VDE approval
- Screwdrivers for Phillips screws with Pozidriv and Phillips Recess screw head



### Key commercial data

Packing unit	1 1
Weight per Piece (excluding packing)	160.0 GRM
Custom tariff number	82054000
Country of origin	Czech Republic

### Technical data

#### Dimensions

Length (b)	262 mm
Width (a)	40 mm
Blade height	150 mm

#### General

Design	Phillips
Type	Straight
Material	Alloyed tool steel
Test standard	DIN/ISO 8764-1 PH IEC 60900:2004

# Screwdriver - SZK PH3 VDE - 1212536

## Classifications

### eCl@ss

eCl@ss 4.0	21040401
eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409
eCl@ss 8.0	21040409

### ETIM

ETIM 4.0	EC000144
ETIM 5.0	EC000144

### UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

## Approvals

### Approvals

---

#### Approvals

VDE Zeichengenehmigung / GOST / GOST

---


#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

VDE Zeichengenehmigung 
--

## Screwdriver - SZK PH3 VDE - 1212536

### Approvals

GOST 

GOST 

### Drawings

Pictogram

