





GENERAL SPECIFICATIONS:

RATING: 10A / 125V AC

CABLE TYPE / SIZE: SJT, # 18 AWG, 3 CONDUCTOR

TEMPERATURE RATING: 60° C MIN.

CONDUCTOR COLORS: BLACK / WHITE / GREEN CABLE JACKET COLOR: PEA GREEN, PANTONE 617U

OVERALL LENGTH (L): 2745 + 50 mm CABLE OUTER DIAMETER: 7.8 ± 0.1 mm END 'A' PLUG; **NEMA 5-15P**

END 'B' SEE TERMINATION TABLE

APPROVALS PLUG: UL, CSA or cUL APPROVALS CABLE: UL. CSA or cUL

CONDUCTOR TERMINATION TABLE:

Wire	Color	ROJ <u>+</u> 3 mm	STRIP <u>+</u> 1mm	TERMINATION		
NEUTRAL	WHITE	153	13	STRIPPED & TINNED		
LINE	BLACK	153	13	STRIPPED & TINNED		
GROUND	GREEN	153	13	STRIPPED & TINNED		



1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS AND/ OR FILE NUMBERS.







NOTES

PACKING:

REV.

PART NO

BULK PACK, BUNDLES OF 25



Contents of this document

prior notice

are subject to change without

UL,CSA or EN Standards installation instruction.



th ts of California SITION 657
n of Hear

DASH

Foot Note:	Limitation of Use:
Globtek Inc. will not be liable for the	Globtek product are not authorized for use
safety and performance of these power sup-	mission critical components in life support,
plies if unauthorized access and repair occurs.	hazardous environment, nuclear or
End user should consult the applicable	aircraft applications without prior written
UL,CSA or EN Standards for proper	approval from the CEO of Globtek Inc.
and the second s	

TABULATION BLOCK											
	TOLERA DECIMALS .xx +/- 0.1 .xxx +/005	ANCES: ANGULAR +/- 1' Www.globtek.com		186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111							
INIT.BY: BS	DATE: 08/02/06	MILLIMETERS .xx +/- 0.3 .xxx +/013	ANGULAR +/- 1°	DWG TITLE: NORTH AMERICAN NON-DETACHABLE CORDSET				ORDSET			
DRAWN: NF	DATE: 08/02/06	FSCN No.: G, CC	SIZE A					REV. A			
APRVD: HM	DATE: 08/02/06	SCALE: N	IONE	PART NO:	3021069F0GN(R)			SHEET 1/1			

DESCRIPTION