

High-Speed HDMI Cable, Gripping Connectors, 4K (M/M), Black, 10 ft. (3.05 m)

MODEL NUMBER: P568-010-BK-GRP











Securely connect your HDMI-enabled laptop or tablet to a TV, monitor or projector for crystal-clear audio and 4K video.

Features

Tripp Lite's 10-ft. (3.05 m) high-speed HDMI cable securely connects HDMI-enabled laptops, tablets, PCs, Blu-ray players, game consoles or satellite/cable TV boxes to HDTVs, HD monitors, projectors or home theater receivers. The gripping connectors help ensure components stay firmly attached to avoid viewing interruptions.

Enjoy the Clarity of 4K HDMI Video with Multi-Channel Audio

Common in home theaters, HDMI allows uncompressed digital video and multi-channel audio signals to travel together in a single cable. This Tripp Lite 4K HDMI cable provides a pure digital connection that supports UHD 4K video resolutions for crystal-clear picture and sound. It is backward compatible with previous HDMI generations, allowing use with lower resolution HDMI components.

Avoid Signal Disruptions with Extra-Secure Connections

Specially designed male connectors firmly grip the HDMI ports on your equipment to help prevent accidental disconnection and signal disruption. With greater port retention than typical HDMI connectors, the gripping connectors resist vibrations that can loosen connections over time. This is especially helpful for ensuring components stay attached in difficult-to-access installations. The gripping connectors are compatible with any full-size HDMI port.

Invest in Quality Construction for Reliable Performance

High-quality materials ensure outstanding performance throughout the cable's lifetime. Contacts and connectors are gold-plated to resist corrosion, and double shielding reduces line noise (EMI/RFI) that can disrupt signals traveling through the HDMI cord.

Highlights

- Connects computers, Blu-ray players or game consoles to HDTVs, HD monitors or receivers
- Supports video resolutions up to 4K for outstanding picture quality
- Firmly grips HDMI ports to prevent accidental disconnects
- 10-ft. (3.05 m) length allows flexibility in home theater setups

Applications

- Connect a laptop or tablet to a 4K TV
- Connect a laptop to a table's A/V connectivity box in a classroom or conference room to present video on a larger screen
- Connect a desktop computer to an HDMI monitor
- Connect a gaming console, like PlayStation (PS3, PS4) or Xbox, to an HDTV
- Connect a Blu-ray disc player to a 4K TV in your home theater
- Use with an Apple digital AV adapter to support iPad2 video mirroring
- Send ultra HD HDMI content to digital signs or point-of-sale displays

Package Includes

 High-Speed HDMI Cable, 10 ft., with Gripping Connectors - 4K, M/M, Black



Design a Home Theater to Your Specifications

This long HDMI cable allows you greater flexibility in placing your home theater components. For instance, your Blu-ray player or video game system may be connected some distance from the display.

The P568-010-BK-GRP is backed by Tripp Lite's lifetime limited warranty.

Specifications

-		
OVERVIEW		
UPC Code	037332209948	
Product Type	Passive	
Technology	HDMI	
VIDEO		
Max Supported Video Resolution	3840 x 2160 @ 30Hz	
Max Supported Color Depth	48-bit Deep Color	
HDR Support	No	
3D Video Supported	Yes	
Chroma Sub Sampling	4:4:4	
EDID Support	Yes	
Signal Transmission	Bidirectional	
AUDIO		
Audio Specification	ARC	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	0	
PHYSICAL		
Color	Black	
Material of Construction	PVC	
Cable Jacket Color	Black	
Connector Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	6.0mm	
Wire Gauge (AWG)	30	



Cable Length (ft.) 10 Cable Length (in) 3.05 Cable Length (in.) 120 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (thed / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (thed / om) 22.86 x 17.78 x 1.27 Shipping Weight (tbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Relative Humidity 0% 5-9%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible CONSUME Electronics Control (OEC) Yes CONNECTIONS Side B - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Spacification 1.4: 2.2 <td< th=""><th></th><th></th></td<>			
Cable Length (in.)	Cable Length (ft.)	10	
Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.0x 7.0 x 0.0 5.0 Shipping Dimensions (hwd / cm) 22.8 x 17.78 x 1.27 Shipping Weight (ks) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 1.40 F (-15 to 60 C) Relative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Supported Ves CONSUMER Electronics Control (CEC) Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Contact Plating Gold Contact Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4, 2.2 EMI/RFI Line Noise Protection No MST Support IP68 Rated No Antibacterial	Cable Length (m)	3.05	
Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (bs.) 0.40 Shipping Weight (bs.) 0.18 ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Ralative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Supported CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMIRFI Line Noise Protection No MST Support No MST Support No Antibacterial No	Cable Length (in.)	120	
Shipping Dimensions (hwd / ini.) 9.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Relative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Communications EDID Compatible Yes EDID Compatible Yes Consumer Electronics Control (CEC) Supported CONNECTIONS Side A - Connector 1 HDMI (MALE) Connector Plating Gold Connector Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4: 2.2 EMURFI Line Noise Protection No MST Support No MST Support No Mnibacterial No	Ferrite Core	No	
Shipping Dimensions (hwd / cm) 22.86 x 17.78 x 1.27	Minimum Bend Radius	30mm	
Shipping Weight (bs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Relative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Skyle Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMURFI Line Noise Protection No MST Support No Antibacterial No	Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50	
Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Relative Humidity 0%- 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes CONSUMER Electronics Control (CEC) Supported Ves CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No MST Support No MST Support No Antibacterial No	Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27	
ENVIRONMENTAL Operating Temperature Range Sto 140 F (-15 to 60 C) Relative Humidity O% - 90%, Non-Condensing Operating Humidity Range O% to 90% RH, Non-Condensing Storage Humidity Range O% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Supported HDMI (MALE) Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Consector Plating Gold Contect Plating Gold Connector Style Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No Intercept A - No Antibacterial No Antibacterial	Shipping Weight (lbs.)	0.40	
Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Relative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No MST Support No Antibacterial No	Shipping Weight (kg)	0.18	
Storage Temperature Range 5 to 140 F (-15 to 60 C) Relative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Supported Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Consector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	ENVIRONMENTAL		
Relative Humidity 0% - 90%, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Supported Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Consector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No Antibacterial No	Operating Temperature Range	14 to 122 F (-10 to 50 C)	
Operating Humidity Range	Storage Temperature Range	5 to 140 F (-15 to 60 C)	
Storage Humidity Range 0% to 90% RH, Non-Condensing COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No Inf68 Rated No Antibacterial No	Relative Humidity	0% - 90%, Non-Condensing	
COMMUNICATIONS EDID Compatible Yes Consumer Electronics Control (CEC) Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No Antibacterial No	Operating Humidity Range	0% to 90% RH, Non-Condensing	
EDID Compatible Yes Consumer Electronics Control (CEC) Yes CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No Antibacterial No	Storage Humidity Range	0% to 90% RH, Non-Condensing	
Consumer Electronics Control (CEC) Supported CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Connector Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	COMMUNICATIONS		
Supported CONNECTIONS Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	EDID Compatible	Yes	
Side A - Connector 1 HDMI (MALE) Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Consumer Electronics Control (CEC) Supported	Yes	
Side B - Connector 1 HDMI (MALE) Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	CONNECTIONS		
Connector Plating Gold Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Side A - Connector 1	HDMI (MALE)	
Contact Plating Gold Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Side B - Connector 1	HDMI (MALE)	
Connector Style Straight Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Connector Plating	Gold	
Latching or Gripping Connector Yes FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Contact Plating	Gold	
FEATURES & SPECIFICATIONS HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Connector Style	Straight	
HDCP Specification 1.4; 2.2 EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	Latching or Gripping Connector	Yes	
EMI/RFI Line Noise Protection No MST Support No IP68 Rated No Antibacterial No	FEATURES & SPECIFICATIONS		
MST Support No IP68 Rated No Antibacterial No	HDCP Specification	1.4; 2.2	
IP68 Rated No Antibacterial No	EMI/RFI Line Noise Protection	No	
Antibacterial No	MST Support	No	
	IP68 Rated	No	
	Antibacterial	No	
Armored Cable No	Armored Cable	No	



Ethernet Support	No	
IP20 Rated	No	
OTANDADDO O COMPLIANOS		
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.