



Cross-connection rail, No. of poles: 3, Mounting type: Can be screwed on, Width: 32 mm, Colour: natural

Business data

| Dusiness data | |
|--|-----------------------|
| Article number | <u>2367.0</u> |
| Article name | QS 3 |
| GTIN (EAN) | 4044211051556 |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 2.4 g |
| Weight per piece (including packaging) | 2.41 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Product description | Cross-connection rail |
| Colour | Natural |

Data sheet





| Technical data | | |
|---------------------------------------|------------|--|
| Dimensions | | |
| Length | 6 mm | |
| Width | 32 mm | |
| Height | 2 mm | |
| Hole diameter | 3.4 mm | |
| Hole spacing (mid-point to mid-point) | 11.9 mm | |
| Pitch size | 12 mm | |
| Connection data | | |
| No. of poles | 3 | |
| Materials | | |
| Material | Brass | |
| Surface | Nickel | |
| Further technical data | | |
| Mounting type | Screwable | |
| Number of bridged terminals | 3 | |
| Environmental Product Compliance | | |
| REACH Conform | yes | |
| REACH Reference date | 2022-06-10 | |
| REACH Candidate Substance Note | No | |
| RoHS Conform | yes | |
| | | |

Data sheet

2367.0 QS 3



Media



Accessories

##INVERSE##CONTA-CONNECT



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|----------------|
| 1004.4 | SK 1/35 24V AC LED(RD) PA-G BK | 4044211129989 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|-------------------|
| 1119.4 | SK 1/35 48V AC LED(RD) PA-G BK | 4044211130008 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------------|---------------|----------------|
| 1375.4 | SK 1/35 230V AC G PA-G BK | 4044211129941 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|-------------------|
| 1380.4 | SK 1/35 24V DC LED(RD) PA-G BK | 4044211129972 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| 1367.4 | SK 1/35 PA-G BK | 4044211128555 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|-------------------|
| 1067.4 | SK 1/35 48V DC LED(RD) PA-G BK | 4044211129996 | 20 ST |

Data sheet

2367.0 QS 3



##INVERSE##CONTA-CONNECT



Fused terminal with screw cap for indicator fuses 5x25 mm, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour:

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------------|---------------|-------------------|
| 1368.4 | SK 1/35 m.K. PA-G BK | 4044211129811 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------------|---------------|----------------|
| <u>1376.4</u> | SK 1/35 115V AC G PA-G BK | 4044211129958 | 20 ST |