

3M

Highland™

Label Protection Tape

3565

Technical Data

April, 2003

Product Description 3M™ Highland™ Label Protection Tape 3565 has a clear, strong, moisture-resistant film backing and a strong adhesive that holds well to many treated and finished surfaces. It is used for the attachment and preservation of identifying labels in shipping, storage, and manufacturing applications.

Construction	Backing	Adhesive	Colors
	3M™ Scotchpro™ polypropylene film	Pressure-sensitive synthetic rubber resin. Requires no moisture, heat, or solvent for activation.	Clear

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	40 oz./in. width (44 N/100 mm width)	D-3330
Tensile Strength:		
Longitudinal:	22 lbs./in. width (385 N/100 mm width)	D-3759
Transverse:	44 lbs./in. width (770 N/100 mm width)	D-3759
Elongation at Break:	160%	D-3759
Thickness Total:	1.9 mil (0.048 mm)	D-3652
Shear Holding to Fiberboard:	3000+ minutes	D-3654

Features

- Adheres instantly to a variety of surfaces.
- Edge tear and split resistance.
- Conformable backing.
- Clear, strong, and moisture-resistant.
- Good adhesion to fiberboard.
- Complies with environmental considerations of ASTM D1974-92.
- Protects labels from abrasion, smudging, splashing, and tearing.

Highland™ Label Protection Tape

3565

Available Sizes	Standard Widths:	2.8 in., 3.8 in., 4.7 in., 5.7 in. (72 mm, 96 mm, 120 mm, 144 mm)
	Core Size (ID):	3 in.
	Lengths:	109 yds. (100 m)

Storage Conditions Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business
Industrial Adhesives and Tapes Division**
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2003 70-0710-0268-0 (4/03)