

# 1550 Standard and 1350 High Inrush

150A to EN61058-1 and 16A 250Vac



## Key Features

- Standard rocker switch
- 1350/53 high inrush
- Choice of switching circuits including 3 position
- Push-on, solder and PCB terminals
- Choice of bezel styles
- Choice of panel cut outs
- Matching indicator
- Double Contact
- Splash resistant option
- Panel cut out 'A' style: 27.2 x 22.3mm

## Approvals and specifications

- ☞ 1550 Series 16(4)A 250Vac T125
- ☞ UL CSA 16A 250Vac, (2 posn) 250Vac 1hp, 125Vac 1/2hp, 1350 72 Vdc 7A (3 posn) 250 Vac 1/2hp, 125Vac 1/4hp. UL 85°C, file E45221, CSA file LR10990.

### In house test:

10A 24Vdc— Indicative rating only. NB Types fitted with Neon will not illuminate for low DC voltage applications.

- ☞ 1350 series 16(4)A 250Vac T85 1E4 (10,000 Ops.)
- ☞ 1330 series 16(6)A 250Vac T125 5E4 (50,000 Ops.)
- ☞ 150A Inrush to EN61058-1.

Terminal	Function	Rocker	Body
<b>C</b>  6.3 x 0.8	<b>Standard 1550</b>  ON - OFF X terminal N/A	<b>A</b> Softline Matt  <b>B</b> Splash resistant Softline  <b>V</b> Curved  Matt or Gloss  Gloss only Lit (not momentary)	Panel cut-out Bezel Cut-outs must be punched in the direction of insertion <b>A</b>  27.2 27.3 22.3/22.4 25.0 30.2 <b>B</b>  30.0 30.1 22.1/22.2 R3.5 25.0 33.4 Matt only
	<b>1551</b> HP rating N/A  ON - OFF (momentary ON)		
<b>H</b>  4.8 x 0.8*	<b>1552</b> HP rating N/A  ON - OFF (momentary OFF)	<b>W</b> Splash resistant Curved  <b>P</b> Lit window Matt  Lit (not momentary) <b>X</b> Two colour Matt  (ON OFF only - not momentary)	<b>L</b>  30.0 30.1 22.1/22.2 R1.0 25.0 32.0 Matt only <b>Q</b>  28.2 28.3 22.3/22.4 R1.6 25.0 30.2 Gloss or matt
	<b>1553</b> Not W, X or B rocker  ON - OFF Lit		
<b>K</b>  2.8 x 0.8*	<b>1560 μ</b>  ON - ON	<b>R</b> Round  <b>F</b> Flat Lens Gloss (0480)  Top View <b>A</b> Softline lens Matt (0480 only) as F but with raised profile 	<b>R</b>  28.4 28.5 25.3/25.4 28.9 33.2 Matt only <b>T</b>  28.2 28.3 22.3/22.4 R1.6 25.0 30.2 Matt only
	<b>1561 μ</b> HP rating N/A  ON - ON (Momentary 1 Side)		
<b>T</b>  Ø2.1 Solder	<b>1570 μ</b> 125V & 250V 1/2 HP H terminal rated T100 only H terminal rated T100 only	<b>T</b>  Ø2.1 Right angle "T" solder terminal	<b>T</b>  Ø2.1 PCB 0.8Sq*
	<b>1571 μ</b> HP rating N/A H terminal rated T100 only		

## Approvals and specifications (continued)

**UL** CSA 20A 250Vac 1hp, 125Vac 1/2hp.  
 UL 72Vdc 7A, 36Vdc 14A.  
 UL 85°C, file E45221, CSA file LR10990.

### In house test:

20A 24Vdc—Indicative rating only

3mm contact gap except if marked  $\mu$ .


## Splash Resistance



### 1300 High inrush, positive break switching

The 1300 series mechanism ensures contact welds formed at switch-on are positively separated by the plunger tube acting directly on the step in the moving contact.

## Dimensions



### Panel thickness

A.Q 0.75 to 3.3mm  
 L.B.T 0.75 to 2.5mm  
 R 0.75 to 3.0mm

\* For cut-out details on momentary switches call sales

Finish	Body Colour	Rocker Colour	Insert Colour	Lamp Voltage	Legend	Legend Colour	Options
<b>M</b> Matt	<b>B</b> Black	Un-Lit	Blank	Blank	Blank	Blank	Finish Matt is standard.  Colour Call sales for custom colours. A full range is available for large orders.  Legend printing Select from the examples or call sales for custom legends.  Lamp voltage Call sales for details.  Blanking plates A0494 Dummy units to fill unused panel holes.  Protective cover Snaps on to A, L, Q or T bodies (add G after body in cat no). This reduces panel thickness by 1mm.
		<b>B</b> Black		<b>2</b> 125V Neon			
<b>G</b> Gloss	<b>W</b> White	<b>R</b> Red	<b>R</b> Red	<b>3</b> 250V Neon	<b>602A</b>	<b>B</b> Black	
		<b>W</b> White	<b>W</b> White	<b>5</b> 12Vdc LED (P Rocker)			
Applies to both Rocker & Body		<b>A</b> Amber	<b>W</b> White	<b>6</b> 24Vdc LED (P Rocker)	<b>7</b> 12V Filament	<b>8</b> 24Vdc Filament	
		<b>G</b> Green		<b>7</b> 12V Filament			
Applies to both Rocker & Body		<b>C</b> Clear	<b>W</b> White	<b>8</b> 24Vdc Filament	<b>8</b> 24Vdc Filament	<b>8</b> 24Vdc Filament	
		<b>R</b> Red					

## Examples



☐ C1350AL ---



☐ C1550XL ---



☐ C1553PL ---



☐ C1553RA ---  
 Shown with M614  
 bezel cover



Optional snap-in  
 M441 barrier




C1553AA with M616  
 guard Cut-out  
 22.0/22.1 x 29.4/29.5  
 Guard accepts "A"  
 body only



☐ C0480RA ---  
 Shown with  
 M614 bezel  
 cover



☐ C0480AL ---



Panel sealing washer W42 is available for the above body sizes. This reduces panel thickness by a further 1.00mm. Covers are not suitable for momentary types.

For all options call sales.

# 1550 Standard & 1350 High Inrush Switches

150A to EN61058-1 and 16A 250Vac/250Vdc



## Key Features

- Standard rocker switch
- 1350/53 high inrush
- Choice of switching circuits including 3 position
- Push-on, solder and PCB terminals
- Choice of bezel styles
- Choice of panel cut outs
- Matching indicator
- Double Contact
- Option with guard & cover
- DC LED Illumination Available for "P" Rocker
- Bezel size 'G' style 32.0 x 25.0

## Approvals and specifications

UL 1550 Series 16(4)A 250Vac T125

UL CSA 16A 250Vac, (2 posn) 250Vac 1hp, 125Vac 1/2hp, (3 posn) 250 Vac 1/2hp, 125Vac 1/4hp. UL 85°C, file E45221, CSA file LR10990.

### In house test:

10A 24Vdc— Indicative rating only

1350 Series

UL CSA 20A 250Vac 1hp, 125Vac 1/2hp. UL 72Vdc 7A, 36Vdc 14A, UL 85°C, file E45221, CSA file LR10990.

Terminal	Function	Rocker	Body	Finish	Body Colour	Rocker Colour	
<b>C</b> 	<b>Standard 1550</b> <b>1551</b> HP rating N/A	 ON - OFF	<b>A</b> Softline Matt 	Panel cut-out Cut-outs must be punched in the direction of insertion <b>B</b>  Matt only	<b>M</b> Matt	<b>B</b> Black	Un-Lit <b>B</b> Black
<b>H</b> 	<b>1552</b> HP rating N/A	 ON - OFF (momentary OFF)			<b>G</b> Gloss	<b>W</b> White	<b>R</b> Red
<b>K</b> 	<b>1553</b> Not W, X or B rocker	 ON - OFF Lit	<b>V</b> Curved Matt or Gloss  Gloss only Lit (not momentary)	<b>L</b>  Matt only	Applies to both Rocker & Body	<b>W</b> White	Lit <b>A</b> Amber
<b>T</b> 	<b>1560 µ</b> <b>1561 µ</b> HP rating N/A	 ON - ON				<b>W</b> White	Lit <b>A</b> Amber
<b>U</b> 	<b>1562 µ</b> In house tests only	 ON - ON (Momentary 1 Side)				<b>W</b> White	Lit <b>A</b> Amber
<b>X</b> 	<b>1570 µ</b> 125V & 250V 1/2 HP H terminal rated T100 only H terminal rated T100 only	 ON - ON (Momentary 2 Sides)	<b>P</b> Lit window Matt  Lit (not momentary)			<b>W</b> White	Lit <b>A</b> Amber
<b>X</b> 	<b>1571 µ</b> HP rating N/A H terminal rated T100 only	 ON - OFF - ON				<b>W</b> White	Lit <b>A</b> Amber
<b>X</b> 	<b>1572 µ</b> HP rating N/A H terminal rated T100 only	 ON - OFF - ON (momentary 2 sides)				<b>W</b> White	Lit <b>A</b> Amber
<b>X</b> 	<b>High Inrush 1350</b> Not W, X or B rocker	 ON - OFF				<b>W</b> White	Lit <b>A</b> Amber
<b>X</b> 	<b>1353</b> Not W, X or B rocker	 ON - OFF Lit				<b>W</b> White	Lit <b>A</b> Amber


### Splash Resistance

**In house test:**  
20A 24Vdc— Indicative rating only  
  
3mm contact gap except if marked  $\mu$ .



**1350 High inrush, positive break switching**  
The 1350 series mechanism ensures contact welds formed at switch-on are positively separated by the plunger tube acting directly on the step in the moving contact.

### Dimensions



**Panel thickness**  
G, H 0.75 to 2.5mm

Terminal spacing - Contacts 10.2 between centres

\* For cut-out details on momentary switches call sales

Insert Colour	Lamp Voltage	Legend	Legend Colour	Options
Blank	Blank	Blank	Blank	<p><b>Finish</b> Matt is standard.</p> <p><b>Colour</b> Call sales for custom colours. A full range is available for large orders.</p> <p><b>Legend printing</b> Select from the examples or call sales for custom legends.</p> <p><b>Lamp voltage</b> Call sales for details.</p>
<b>R</b> Red	<b>2</b> 125V Neon	<b>602A</b>	<b>B</b> Black	
<b>W</b> White	<b>3</b> 250V Neon		<b>W</b> White	
	<b>5</b> 12Vdc LED (P Rocker)			
	<b>6</b> 24Vdc LED (P Rocker)			
	<b>7</b> 12V Filament			
	<b>8</b> 24Vdc Filament			

### Examples



C1553AH - - -



C1550AH - - -