

## Han-Yellock 30 Hood-M32 angled



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 11 12 300 1602  |
| Specification      | Han-Yellock 30 Hood-M32 angled  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/11123001602">https://b2b.harting.com/11123001602</a> |

### Identification

|                          |                |
|--------------------------|----------------|
| Category                 | Hoods/Housings |
| Series of hoods/housings | Han-Yellock®   |
| Type of hood/housing     | Shell          |

### Version

|                      |  |
|----------------------|--|
| Size                 | Han-Yellock® 30                            |
| Version              | Angled entry                               |
| Cable entry          | 1x M32                                     |
| Locking type         | Push button                                |
| Field of application | Hoods/housings for industrial applications |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Un-/locking temperature                | -10 ... +85 °C                                 |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67                                   |

### Material properties

|                         |                                   |
|-------------------------|-----------------------------------|
| Material (hood/housing) | Aluminium die-cast                |
| Surface (hood/housing)  | Powder-coated                     |
| Colour (hood/housing)   | RAL 7021 (black grey)             |
| Material (locking)      | Polyamide (PA)<br>Stainless steel |



Pushing Performance  
Since 1945

## Material properties

|   |                       |
|---|-----------------------|
| Material flammability class acc. to UL 94 | V-0                   |
| RoHS                                      | compliant             |
| ELV status                                | compliant             |
| China RoHS                                | e                     |
| REACH Annex XVII substances               | Not contained         |
| REACH ANNEX XIV substances                | Not contained         |
| REACH SVHC substances                     | Not contained         |
| California Proposition 65 substances      | Yes                   |
| California Proposition 65 substances      | Nickel<br>Naphthalene |

## Specifications and approvals

|                |                          |
|----------------|--------------------------|
| Specifications | IEC 60664-1<br>IEC 61984 |
| Approvals      | DNV GL                   |
| CE             | Yes                      |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 106.2 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140110106                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |