

Specification Sheet

Part Number: 111-02447



Made from PVDF for high UV, chemical and thermal resistance. Inside serrations deliver secure hold on cable and wire bundles.

Head design provides high tensile strength with low insertion force.

PVDF Cable Tie, 8" Long, 50lb Tensile Strength, PVDF, Gray, 3000/ctn

Article Number 111-02447

Type T50R

Color Gray (GY)

Quantity Per carton

Product Description The PVDF cable tie is rated for 25 years' performance outdoors. It provides some of the highest UV, chemical and thermal resistance of any plastic resin. It functions just like our standard ties, simple and fast, streamlining installation and providing reliable performance.

Short Description PVDF Cable Tie, 8" Long, 50lb Tensile Strength, PVDF, Gray, 3000/ctn

Global Part Name T50R-PVDF-GY

| | |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 200.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.19 |
| Width W (Metric) | 4.7 |
| Bundle Diameter Min (Imperial) | 0.31 |
| Bundle Diameter Min (Metric) | 8.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Thickness T (Imperial) | 0.47 |
| Thickness T (Metric) | 1.2 |

| | |
|------------------------------|-----------------------------------|
| Material | Polyvinylidene Fluoride (PVDF) |
| Material Shortcut | PVDF |
| Flammability | UL 94 V-0 |
| Operating Temperature | -40°F to +284°F (-40°C to +140°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 3000 |
| Package Quantity (Metric) | 3000 |
| Customs Number | 3926909988 |