

EEM-MEMO-MA600


Order No.: 2901370



<http://eshop.phoenixcontact.ae/phoenix/treeViewClick.do?UID=2901370>

Storage module for intermediate storage of values (512 kB) for EEM-MA600

Commercial data

EAN	 4 046356 585798
Pack	1 pcs.
Customs tariff	90303100
Gross weight in pieces	132.30 g

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Input data

Description of the input	Optocoupler input
Number	1
Voltage input signal	10 V DC ... 30 V DC
Input pulse length	≥ 1 s
Peak offstate voltage	30 V DC
Memory size	512 kByte

General data

Width	22.5 mm
Height	65 mm
Depth	48 mm
Supply voltage	9 V (via EEM-MA600)

Degree of protection	IP20
Color	black
Conformance	CE-compliant
Rated insulation voltage at mains voltage < 300 V AC (L/N)	III
Rated insulation voltage at mains voltage > 300 V AC - 600 V AC (L/N)	II
Test voltage	3.5 kV AC (50 Hz, 1 min.)
Ambient temperature (operation)	-10 °C ... 55 °C (14 °F to 131 °F)
Ambient temperature (storage/transport)	-20 °C ... 85 °C (-4 °F ... 185 °F)
Max. permissible relative humidity (operation)	≤ 95 %
Salt spray	≤ 2.5 %

Connection data

Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	14
Connection method	COMBICON plug-in screw terminal block
Stripping length	6 mm
Tightening torque	0.4 Nm

Certificates



Certification

cULus Listed

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Middle East FZ LLC
Office 301, Third Floor, Block 10, Dubai International
Academic City (DIAC)
Dubai, United Arab Emirates
Phone +971 4 437 0324
Fax +971 4 437 0323
<http://www.phoenixcontact.com>

PHOENIX CONTACT Middle East FZ LLC
Technical modifications reserved;