1 METER LENGTH

recent fr

Connector A 132453 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm LMR-240 Continuity/Hi-Pot Connector B 132452 SMA Plug Right Angle Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Right Angle	Connector A			Cable			Connector B		
	90° 45° 0° 225° 270° 315° Eulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132453	R240 Optimized 50O Vlount	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	LMR-240 LMR-240 - FEP 0.24 FEP Braid 0.24 50 Ohm None Continuity Hi-Pot 1 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	132452	IR240 Optimized 50O	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY			THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED DF ING Part No:	SMA-ST-JK/SMA-RA-PL LMR24 1M Part No:		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES		