

Crimping pliers - CRIMPFOX 6T - 1212037

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Crimping pliers, for ferrules as per DIN 46228 section 1+4, 0.5 - 6 mm², insertion from the side, trapezoidal crimp

Why buy this product

- Comprehensive range of crimping pliers
- All ferrules can be optimally crimped with a minimum amount of effort even in the case of large conductor cross sections
- Marked die stations for precise processing of corresponding cross sections
- Consistently high crimping quality
- Unlockable pressure lock

Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 269 (CL2-2011)
GTIN	 4 046356 454049
Custom tariff number	82032000
Country of origin	SWEDEN

Technical data

General

Length (b)	220 mm
Height	72 mm
Width (a)	22.5 mm
Color	black
Weight	555 g
Die station	Crimping position 1
Min. cross section	0.25 mm ²
Max. cross section	6 mm ²
AWG min	24
AWG max	10
Die station	Crimping position 2
Die station	Crimping position 3

Crimping pliers - CRIMPFOX 6T - 1212037

Technical data

General

Die station	Crimping position 4
Die station	Crimping position 5
Compression	Trapezoidal crimp
Type of contact	Ferrules

Classifications

eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811

etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details

Crimping pliers - CRIMPFOX 6T - 1212037

Approvals



Accessories

Accessories

Tools

Accessories - CRIMPFOX 6T/DIE - 1212298

Spare die for CRIMPFOX 6T

Replacement spring - CRIMPFOX/ SPR-1 - 1212069



Spare recuperating spring

Drawings

Product drawing

