

**MMSZ5221B-MMSZ5267B ZENER DIODES**



**Features**

- Planar Die Construction
- 500mW Power Dissipation
- 2.4V- 75V Standoff Voltage
- 5% Nominal Zener Voltage
- Designed for Surface Mount Application
- Plastic Material-UL Recognition Flammability Classification 94V-0
- This is a Halogen Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

**Circuit Diagram**



**Mechanical Data**

- Case: SOD-123, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.01 grams(approx)

**Maximum Ratings @T<sub>A</sub>=25°C unless otherwise specified**


Characteristic	Symbol	Value	Units
Power Dissipation (Note 1)	P <sub>D</sub>	500	mW
Forward Voltage (Note 2) @ I <sub>F</sub> = 10mA	V <sub>F</sub>	0.9	V
Typical Thermal resistance junction to Ambient Air	R <sub>θJA</sub>	357	°C/W
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to 150	°C

Notes: 1. Device mounted on ceramic PCB; 7.6 mm x 9.4 mm x 0.87 mm with pad areas 25 mm<sup>2</sup>.  
2. Tested with pulses, Tp≤1.0ms.


**Electrical Characteristics @T<sub>A</sub>=25°C unless otherwise specified**

Device	Device Marking Code	V <sub>Z</sub> @ I <sub>ZT</sub> *1			I <sub>ZT</sub> mA	Z <sub>ZT</sub> @ I <sub>ZT</sub> Max(Ω)	Z <sub>ZK</sub> @ I <sub>ZK</sub> Max(Ω)	I <sub>ZK</sub> mA	I <sub>R</sub> Max(μA)	V <sub>R</sub> V
		Nom(V)	Min(V)	Max(V)						
MMSZ5221B	C1	2.4	2.28	2.52	20	30	1200	0.25	100	1
MMSZ5223B	C3	2.7	2.57	2.84	20	30	1300	0.25	75	1
MMSZ5225B	C5	3	2.85	3.15	20	30	1600	0.25	50	1
MMSZ5226B	G1	3.3	3.14	3.47	20	28	1600	0.25	25	1
MMSZ5227B	G2	3.6	3.42	3.78	20	24	1700	0.25	15	1
MMSZ5228B	G3	3.9	3.71	4.10	20	23	1900	0.25	10	1
MMSZ5229B	G4	4.3	4.09	4.52	20	22	2000	0.25	5	1
MMSZ5230B	G5	4.7	4.47	4.94	20	19	1900	0.25	5	2
MMSZ5231B	E1	5.1	4.85	5.36	20	17	1600	0.25	5	2
MMSZ5232B	E2	5.6	5.32	5.88	20	11	1600	0.25	5	3
MMSZ5233B	E3	6.0	5.70	6.30	20	7	1600	0.25	5	3.5
MMSZ5234B	E4	6.2	5.89	6.51	20	7	1000	0.25	5	4
MMSZ5235B	E5	6.8	6.46	7.14	20	5	750	0.25	3	5
MMSZ5236B	F1	7.5	7.13	7.88	20	6	500	0.25	3	6
MMSZ5237B	F2	8.2	7.79	8.61	20	8	500	0.25	3	6.5
MMSZ5238B	F3	8.7	8.27	9.14	20	8	600	0.25	3	6.5
MMSZ5239B	F4	9.1	8.65	9.56	20	10	600	0.25	3	7
MMSZ5240B	F5	10	9.50	10.50	20	17	600	0.25	3	8
MMSZ5241B	H1	11	10.45	11.55	20	22	600	0.25	2	8.4
MMSZ5242B	H2	12	11.40	12.60	20	30	600	0.25	1	9.1
MMSZ5243B	H3	13	12.35	13.65	9.5	13	600	0.25	0.5	9.9
MMSZ5244B	H4	14	13.30	14.70	9	15	600	0.25	0.1	10
MMSZ5245B	H5	15	14.25	15.75	8.5	16	600	0.25	0.1	11
MMSZ5246B	J1	16	15.20	16.80	7.8	17	600	0.25	0.1	12
MMSZ5247B	J2	17	16.15	17.85	7.4	19	600	0.25	0.1	13
MMSZ5248B	J3	18	17.10	18.90	7	21	600	0.25	0.1	14
MMSZ5250B	J5	20	19.00	21.00	6.2	25	600	0.25	0.1	15
MMSZ5251B	K1	22	20.90	23.10	5.6	29	600	0.25	0.1	17
MMSZ5252B	K2	24	22.80	25.20	5.2	33	600	0.25	0.1	18
MMSZ5253B	K3	25	23.75	26.25	5	35	600	0.25	0.1	19
MMSZ5254B	K4	27	25.65	28.35	5	41	600	0.25	0.1	21
MMSZ5255B	K5	28	26.60	29.40	4.5	44	600	0.25	0.1	21
MMSZ5256B	M1	30	28.50	31.50	4.2	49	600	0.25	0.1	23
MMSZ5257B	M2	33	31.35	34.65	3.8	58	700	0.25	0.1	25
MMSZ5258B	M3	36	34.20	37.80	3.4	70	700	0.25	0.1	27
MMSZ5259B	M4	39	37.05	40.95	3.2	80	800	0.25	0.1	30
MMSZ5260B	M5	43	40.85	45.15	3.0	93	900	0.25	0.1	33
MMSZ5261B	N1	47	44.65	49.35	2.7	105	1000	0.25	0.1	36
MMSZ5262B	N2	51	48.45	53.55	2.5	125	1100	0.25	0.1	39
MMSZ5263B	M8	56	53.2	58.8	2.2	150	1300	0.25	0.1	43
MMSZ5265B	N5	62	58.9	65.1	2.0	185	1400	0.25	0.1	47
MMSZ5267B	P2	75	71.25	78.75	1.7	270	1700	0.25	0.1	56


**Ratings and Characteristics Curves**




**TYPICAL FORWARD VOLTAGE**




**EFFECT OF ZENER VOLTAGE ON ZENER IMPEDANCE**




**POWER DISSIPATION VS. AMBIENT TEMP**




**TYPICAL CAPACITANCE**




**ZENER BREAKDOWN CHARACTERISTICS**



**ZENER BREAKDOWN CHARACTERISTICS**



**Mechanical Dimensions SOD-123**



SYMBOL	Millimeters		Inches	
	MIN.	MAX.	MIN.	MAX.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.450	0.650	0.018	0.026
c	0.080	0.150	0.003	0.006
D	1.500	1.700	0.059	0.067
E	2.600	2.800	0.102	0.110
E1	3.550	3.850	0.140	0.152
L	0.500 REF.		0.020 REF.	
L1	0.250	0.450	0.010	0.018
θ	0°	8°	0°	8°


Note: If date code is before 2016 year, please contact with factory about marking.

**Ordering Information**

Device	Package	Shipping
MMSZ5221B-MMSZ5267B	SOD-123	3000pcs / reel
MMSZ5221BTR-MMSZ5267TR	SOD-123	3000pcs / reel


For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

**Marking Diagram**



C1 = Device Marking Code

**Carrier Tape Specification SOD-123**



SYMBOL	Millimeters	
	Min.	Max.
A	1.80	1.90
B	3.89	3.99
C	1.52	1.62
d	1.45	1.65
E	1.65	1.85
F	3.40	3.60
P	3.90	4.10
P0	3.90	4.10
P1	1.90	2.10
W	7.90	8.30

**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..