



NOTES:

- 1) DIMENSIONS IN [ ] ARE MILLIMETERS
- 2) 5 PIN CYLINDER
- 3) AVAILABLE WITH CUSTOM KEYING
- 4) SHORT SHACKLE IS STANDARD  
ADD "-LS" FOR LONG SHACKLE

	DIM "A"	DIM "B"	DIM "C"	DIM "D"	DIM "E"	DIM "F"
PSL-16A	0.94 [ 23.8 ]	0.93 [ 23.6 ]	0.47 [ 12.0 ]	0.44 [ 11.2 ]	0.17 [ 4.2 ]	0.39 [ 9.9 ]
PSL-16B	1.12 [ 28.4 ]	1.03 [ 26.1 ]	0.56 [ 14.2 ]	0.56 [ 14.2 ]	0.19 [ 4.9 ]	0.52 [ 13.3 ]
PSL-16C	1.50 [ 38.0 ]	1.28 [ 32.4 ]	0.81 [ 20.5 ]	0.83 [ 21.1 ]	0.26 [ 6.5 ]	0.52 [ 13.2 ]
PSL-16C-LS	1.50 [ 38.0 ]	1.28 [ 32.4 ]	0.81 [ 20.5 ]	2.49 [ 63.2 ]	0.26 [ 6.5 ]	0.52 [ 13.2 ]
PSL-16D	1.69 [ 43.1 ]	1.28 [ 32.6 ]	0.95 [ 24.2 ]	0.98 [ 24.8 ]	0.24 [ 6.1 ]	0.54 [ 13.8 ]
PSL-16E	1.88 [ 47.8 ]	1.43 [ 36.4 ]	1.00 [ 25.3 ]	0.92 [ 23.4 ]	0.28 [ 7.2 ]	0.55 [ 13.9 ]
PSL-16F	2.27 [ 57.7 ]	1.71 [ 43.5 ]	1.26 [ 32.1 ]	1.24 [ 25.4 ]	0.33 [ 8.4 ]	0.63 [ 16.0 ]

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	TITLE				SIZE	
							PSL-16 Series All Weather Padlocks					
							CUSTOMER DRAWING					
							ITEM REVISION NAME 00220NCT/00				<b>PANDUIT</b>	
							DATASET FILE NAME 00220NCT_C11718/00A					
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ] .x ± .25 [ 6.35 ]      .xxx ± .05 [ 1.27 ] .xx ± .15 [ 3.81 ]      ANGLES ± 5 °					
							THIRD ANGLE PROJECTION				MATERIAL:  Brass & Steel	
00	02/08/2018	AUMA	DJW	JHAC	Initial Release	GAECN05190	DRAWING NUMBER: C11718					
							DRAWN BY AUMA	DATE 1/30/18	CHK JHAC	SCALE 1:1	SHT 1 OF 1	A