HellermannTyton

Specification Sheet

Part Number: SNP1.5GHS0M4

Installation and removal can be five times faster than conventional clamps

.

Heat stabilized material is suitable for high temperature applications.

Completely reusable

.

Will not rust or corrode

.

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place

One-hand installation for tight places.

Snapper Hose Clamp, 0.32 - 0.35" Bundle Diameter, PA66GF13, Black, 1000/pkg

Article Number

190-00035

Type

SNP1.5

Color

Black (BK)

Quantity Per	
Product Description	

The Snapper Hose Clamp features a ratchet-style closure for reduced assembly time. It can be added after connection of the hose. Release by sliding the ratchet ends apart. Snappers can be used in under-hood applications and are stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and greases. They are manufactured in black PA66 glass filled, impact modified, heat stabilized material. Custom design and color options are available based upon application and volume requirements.

Short Description

Snapper Hose Clamp, 0.32 - 0.35" Bundle Diameter, PA66GF13, Black, 1000/pkg

Global Part Name

SNP1.5-PA66GF13-BK

Fixation Method

Plug-in mounting

Variant

Closed

bag

Bundle Diameter Min (Imperial)

0.31

Bundle Diameter Min (Metric)

8.0

Bundle Diameter Max (Imperial)

0.35

Bundle Diameter Max (Metric)

8.9

Wall Thickness WT (Imperial)

.055

Wall Thickness WT (Metric)

1.414

Material Polyamide 6.6 glass filled impact modified heat stabilized

(PA66GF13%)

Material Shortcut PA66GF13

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions