

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** **0472720026**  
**Status:** **Active**  
**Overview:** DisplayPort\* and Mini DisplayPort Interconnect System  
**Description:** 0.50mm Pitch DisplayPort\* Male Receptacle, Right Angle, Surface Mount, 0.76µm Gold (Au) Plating, 20 Circuits, without Cover, Mylar, Flange or Peg; with Latch Holes and Solder Tab of Shell, Lead-Free

**Documents:**

[3D Model](#) [Packaging Specification PK-47272-001 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)  
[Product Specification PS-47272-001-001 \(PDF\)](#)

**Agency Certification**

UL E29179

**General**

Product Family I/O Connectors  
Series [47272](#)  
Application Wire-to-Board  
Comments Without Post  
Component Type Receptacle  
Overview [DisplayPort\\* and Mini DisplayPort Interconnect System](#)  
Product Name DisplayPort\*  
Type N/A  
UPC 883906135300

**Physical**

Circuits (Loaded) 20  
Circuits (maximum) 20  
Color - Resin Black  
Flammability 94V-0  
Gender Male  
Keying to Mating Part Yes  
Lock to Mating Part Yes  
Material - Metal Copper Alloy  
Material - Plating Mating Gold  
Material - Plating Termination Tin-Bismuth  
Material - Resin High Temperature Thermoplastic  
Net Weight 2.719/g  
Number of Rows 2  
Orientation Right Angle  
PCB Locator Yes  
PCB Retention Yes  
Packaging Type Embossed Tape on Reel  
Panel Mount Without Flange  
Pitch - Mating Interface 0.50mm  
Pitch - Termination Interface 0.50mm  
Plating min - Mating 0.762µm  
Plating min - Termination 1.016µm  
Polarized to Mating Part Yes  
Polarized to PCB Yes  
Ports 1  
Temperature Range - Operating -20°C to +85°C  
Termination Interface: Style Surface Mount  
Waterproof / Dustproof No

**Electrical**



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per  
-ED/01/2017 (12  
January 2017)

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

RoHS Phthalates

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[47272](#) Series

**Mates With**

[47271](#) Plug Sub-Assemblies, [68783](#) Cable Series

Current - Maximum per Contact	0.5A
Grounding to Panel	Yes
Shielded	Yes
Voltage - Maximum	40V AC

**Solder Process Data**

Duration at Max. Process Temperature (seconds)	010
Lead-freeProcess Capability	REFLOW
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	250

**Material Info****Reference - Drawing Numbers**

Electrical Model Document	EE-47272-001, EE-47272-002
Packaging Specification	PK-47272-001
Product Specification	PS-47272-001-001
Sales Drawing	SD-47272-001

\* DisplayPort is a Trademark of VESA

This document was generated on 03/20/2017

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**