



## Convenient Pressure Testing with an Easy-to Read Display, Built-in Magnet and Intuitive Interface



### Functions

- Range of -60 to +60 inH<sub>2</sub>O
- Differential pressure

### Features

- Dual input differential measurement to ±60 inches of water column
- Measures in 11 scales; inH<sub>2</sub>O, psi, bar, mBar, kPa, inHG, mmHG, oz/in<sup>2</sup>, FtH<sub>2</sub>O, cmH<sub>2</sub>O and kgcm.
- Magnetic mount
- Auto ranging
- Backlit display
- Data hold
- Min/Max
- Zero button
- 1-Year limited warranty

### Applications

- Validate pressures in accordance with equipment manufacturer's specification for optimal system efficiency and safety.
- Measure draft, gas supply, manifold or burner pressures
- Dual input offers users the ability to measure pressure drops across heat exchangers, cooling coils, supply and return registers and filters





### Includes

- Flexible transparent silicone tubing (2) 18" length 1/4" diameter
- Barbed gas valve fitting (2)
- Soft pouch (7.48" x 4.33" x 1.96")
- Manual
- Battery

### Specifications

Unit of Measure	Range	Resolution	Accuracy (77 °F)
bar	± 0.200	0.001	± 0.5% Full Scale Output
oz per in <sup>2</sup>	± 46.60	0.01	
psi	± 2.900	0.001	
inHg	± 5.904	0.001	
mBar	± 200.0	0.1	
mmHg	± 150.0	0.1	
kPa	± 20.00	0.01	
Kg per Sq. cm	± 0.204	0.001	
InH <sub>2</sub> O	± 60	0.01	
FtH <sub>2</sub> O	± 6.689	0.001	
cmH <sub>2</sub> O	± 203.9	0.1	

### Downloads



**Manual**



**Data Sheet**

H28-244



Made in CHINA