

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



CHARX connect universal, Vehicle charging inlet, for charging with alternating current (AC) and with direct current (DC), CCS type 1, IEC 62196-2, IEC 62196-3, 125 A / 1000 V (DC), 48 A / 250 V (AC), Single wires, length: 2 m, locking actuator: 12 V, 4-pos., Front and rear mounting, M6, housing: black, A protective cap is supplied as standard for the DC and AC contacts.

## Product Description

Vehicle charging inlet for charging with alternating current (AC) and direct current (DC), compatible with type 1 AC and CCS vehicle charging connectors (EVSE), for installation in electric vehicles for electromobility (EV).

## Your advantages

- Complete product range
- Uniform, space-saving dimensions for the installation space and the screw connection points of all Phoenix Contact vehicle charging inlets
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Safe against overheating with temperature measurement at every DC power contact
- Integrated interlock during charging
- Manual emergency release of the locking actuator
- Protected and sealed against dirt and water with a high degree of protection

## Commercial Data

Item number	1194398
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	A17
Product Key	XWCAIB
GTIN	4063151249267
Weight per Piece (including packing)	4,170 g
Weight per Piece (excluding packing)	4,170 g
Customs tariff number	85444290
Country of origin	PL

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

## Technical Data

### Notes

General	A protective cap is supplied as standard for the DC and AC contacts.
---------	--

### Product properties

Product type	Vehicle charging inlet
Application	for charging with alternating current (AC) and with direct current (DC) for installation in electric vehicles (EV)
Locking type	Locking in the inserted state with a locking mechanism
Technology	Combined Charging System
Charging standard	CCS type 1
Charging mode	Mode 2, 3, 4

### Electrical properties

Type of signal transmission	Pulse width modulation with modulated Powerline communication in accordance with ISO/IEC 15118 / DIN SPEC 70121
Note on the connection method	Crimp connection, cannot be disconnected
Insulation resistance	> 200 MΩ
Coding	2.7 kΩ (between PE and CS)
Temperature measurement	DC contacts: 2x PT1000 (DIN EN 60751)
Temperature monitoring	AC contacts: PTC chain (DIN EN 60738-1)
Type of charging current	AC single-phase
Charging power	12 kW
Charging current	48 A
Type of charging current	DC
Charging power	125 kW
Charging current	125 A

### Power contact

Number	5 (L1, N, PE, DC+, DC-)
Rated voltage	250 V AC
	1000 V DC
Rated current	48 A AC
	125 A DC

### Signal contact

Number	2 (CP, CS)
Rated voltage	30 V AC
Rated current	2 A

### Temperature sensors (PTC chain)

Sensor type	PTC chain
-------------	-----------

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

Standards/regulations	DIN EN 60738-1
Attachment point	Sensor for the AC contacts
Messbereich_Widerstand	790 Ω ... 1420 Ω
Resistance	max. 1200 Ω ±5 K
Ambient temperature	-40 °C ... 130 °C (Operation)

## Temperature sensors (Pt 1000)

Sensor type	Pt 1000
Standards/regulations	DIN EN 60751
Attachment point	2 sensors for the DC contacts

## Locking actuator

Operating voltage	12 V
Note number of positions	4-pos.
Position of the locking actuator	top center

## Locking actuator

Operating voltage	12 V
Note number of positions	4-pos.
Position of the locking actuator	top center
Possible power supply range at the motor	9 V ... 16 V
Maximum voltage for locking detection	12 V
Typical motor current for locking	0.25 A
Reverse current of the motor	max. 1.5 A
Max. dwell time with reverse current	1 s
Recommended adaptation time	600 ms
Pause time after entry or exit path	3 s
Service life insertion cycles	> 10000 load cycles
Lock recognition	available
Mechanical emergency release	available
Ambient temperature (operation)	-40 °C ... 80 °C

## Dimensions

Dimensional drawing	
Bore dimensions	117.6 mm x 90 mm, 117.6 mm x 83 mm
Width	108 mm
Height	151.2 mm
Depth	122.8 mm

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

## Material specifications

Color (Housing)	black (9005)
Color (Mating face)	black (9005)
Material (Housing)	Plastic
Material (Contact surface)	Silver

## Cable / line

Cable length	2 m
Cable type	Single wires

### Single-core wires for AC

Cable length	2 m
Cable structure	2 x 6 mm <sup>2</sup>
Single wire, material	Silicone
Single wire, color	OG
External cable diameter	12.6 mm ±0.2 mm
Cable resistance	≤ 3.2 Ω/km

### Single-core wires for DC

Cable length	2 m
Cable structure	2 x 35 mm <sup>2</sup>
Single wire, material	Silicone
Single wire, color	OG
External cable diameter	14.1 mm ±0.3 mm
Cable resistance	≤ 0.527 Ω/km

### Single-core wire for PE

Cable length	2 m
Cable structure	1 x 25 mm <sup>2</sup>
Single wire, material	Silicone
Single wire, color	GN/YE
External cable diameter	8.6 mm ±0.1 mm
Cable resistance	≤ 0.743 Ω/km

### Single-core wires for locking actuator

Cable length	1 m
Cable structure	4 x 0.5 mm <sup>2</sup>
Single wire, material	PVC
Single wire, color	BU/RD, BU/GN, BU/YE, BU/BN
External cable diameter	1.6 mm ±0.20 mm
Cable resistance	≤ 37.1 Ω/m

### Single-core wires for PTC temperature sensors

Cable length	1 m
Cable structure	5 x 0,5 mm <sup>2</sup>

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

Single wire, color	BN/GY
	BN/YE/GN
External cable diameter	1.6 mm ±0.20 mm
Cable resistance	≤ 37.1 Ω/m

## Single-core wires for Pt 1000 temperature sensors

Cable length	1 m
Cable structure	3 x 0.5 mm <sup>2</sup>
Single wire, material	PVC
Single wire, color	BN
	GN
	YE
External cable diameter	1.6 mm ±0.20 mm
Cable resistance	≤ 37.1 Ω/m

## Single-core wires for communication

Cable length	1 m
Cable structure	2 x 0.5 mm <sup>2</sup>
Single wire, material	PVC
Single wire, color	BK
	WH
External cable diameter	1.6 mm ±0.20 mm
Cable resistance	≤ 37.1 Ω/m

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	> 10000
Insertion force	< 100 N
Withdrawal force	< 100 N

## Environmental and real-life conditions

### Ambient conditions

Degree of protection Vehicle charging inlet	IP55 (plugged in; when plugged in and ready to operate, the degree of protection is only ensued if both plug-in components are original products from Phoenix Contact or suitable standard-compliant products)
	IP67 (Inner area of vehicle charging inlet)
Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	4000 m (above sea level)

## Standards and regulations

### Standards

Standards/regulations	IEC 62196-2
	IEC 62196-3

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

	SAE J1772
--	-----------

## Mounting

Mounting type	Front and rear mounting (0 to 90 degree frontal inclination possible)
Mounting hole diameter	6.70 mm (ø)
Fixing screws	M6
Screws included in the scope of delivery	none


# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1

1194398

<https://www.phoenixcontact.com/us/products/1194398>


## Drawings

Connection diagram



## Installation positions

Connection diagram



## Pin assignment of vehicle charging inlets


# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

Schematic diagram




Temperature sensor technology resistance range at AC contacts




# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1

1194398

<https://www.phoenixcontact.com/us/products/1194398>



Detection for Vehicle Connector




The Combined Charging System (CCS) principle - standard-compliant charging system for electric vehicles, which supports both conventional AC charging and fast DC charging. Both Vehicle Connectors fit into the CCS Vehicle Inlet.

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1

1194398

<https://www.phoenixcontact.com/us/products/1194398>




Locking states of the locking actuator

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1

1194398

<https://www.phoenixcontact.com/us/products/1194398>

## Schematic diagram




## Operating instructions

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1

1194398


<https://www.phoenixcontact.com/us/products/1194398>

Dimensional drawing



Dimensional drawing

Schematic diagram



Block diagram of the locking actuator


# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

Diagram



Pt 1000 characteristic curve at an ambient temperature of 25°C for temperature measurement at the DC contacts

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

## Approvals



**cULus Recognized**

Approval ID: E473195-20210730

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

## Classifications

### ECLASS

ECLASS-9.0	27144706
ECLASS-10.0.1	27144706
ECLASS-11.0	27144706

# Vehicle charging inlet - CHARX T1HBI12-1AC48DC125-2,0M1



1194398

<https://www.phoenixcontact.com/us/products/1194398>

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
	DOT 15571-58-1
	Dechlorane Plus
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)