

**COMPLEMENTARY MEDIUM-POWER HIGH VOLTAGE  
 POWER TRANSISTORS**

... designed for high-speed switching and linear amplifier application for high-voltage operational amplifiers, switching regulators, converters, deflection stages and high fidelity amplifiers.

**FEATURES:**


- \* Continuous Collector Current -  $I_C = 2$  A
- \* Power Dissipation -  $P_D = 35$  W @  $T_C = 25^\circ\text{C}$
- \*  $V_{CE(SAT)} = 0.75$  V (Max.) @  $I_C = 1.0$  A,  $I_B = 125$  mA

| NPN    | PNP    |
|--------|--------|
| 2N3583 | 2N6420 |
| 2N3584 | 2N6421 |
| 2N3585 | 2N6422 |
| 2N4240 | 2N6423 |

1.0 AND 2.0 AMPERE  
 POWER TRANSISTOR  
 COMPLEMENTARY SILICON  
 175-300 VOLTS  
 35 WATTS


**MAXIMUM RATINGS**

| Characteristic  | Symbol         | 2N3583      | 2N3584     | 2N3585 | 2N4240 | Unit                     |
|---|----------------|-------------|------------|--------|--------|--------------------------|
|   |                | 2N6420      | 2N6421     | 2N6422 | 2N6423 |                          |
| Collector-Emitter Voltage   | $V_{CEO}$      | 175         | 250        | 300    | 300    | V                        |
| Collector-Base Voltage  | $V_{CBO}$      | 250         | 375        | 500    | 500    | V                        |
| Emitter-Base Voltage  | $V_{EBO}$      | 6           |            |        |        | V                        |
| Collector Current-Continuous<br>Peak  | $I_C$          | 1.0<br>5.0  | 2.0<br>5.0 |        |        | A                        |
| Base Current  | $I_B$          | 1.0         |            |        |        | A                        |
| Total Power Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 35<br>0.2   |            |        |        | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Junction<br>Temperature Range                                   | $T_J, T_{STG}$ | -65 to +200 |            |        |        | $^\circ\text{C}$         |



**THERMAL CHARACTERISTICS**


| Characteristic                      | Symbol          | Max | Unit               |
|-------------------------------------|-----------------|-----|--------------------|
| Thermal Resistance Junction to Case | $R_{\theta jc}$ | 5.0 | $^\circ\text{C/W}$ |



PIN 1. BASE  
 2. EMITTER  
 COLLECTOR (CASE)

| DIM | MILLIMETERS |       |
|-----|-------------|-------|
|     | MIN         | MAX   |
| A   | 30.60       | 32.52 |
| B   | 13.85       | 14.16 |
| C   | 6.54        | 7.22  |
| D   | 9.50        | 10.50 |
| E   | 17.26       | 18.46 |
| F   | 0.76        | 0.92  |
| G   | 1.38        | 1.65  |
| H   | 24.16       | 24.78 |
| I   | 13.84       | 15.60 |
| J   | 3.32        | 3.92  |
| K   | 4.86        | 5.34  |

FIGURE -1 POWER DERATING



ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$  unless otherwise noted)

| Characteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|

## OFF CHARACTERISTICS

|  |               |                          |  |    |
|--|---------------|--------------------------|--|----|
| Collector - Emitter Sustaining Voltage (1)<br>( $I_C = 200\text{ mA}$ , $I_B = 0$ ) NPN<br>2N3583,2N6420<br>2N3584,2N6421<br>( $I_C = 50\text{ mA}$ , $I_B = 0$ ) PNP<br>2N3585,2N6422<br>2N4240,2N6423  | $V_{CE(SUS)}$ | 175<br>250<br>300<br>300 |  | V  |
| Collector Cutoff Current<br>( $V_{CE} = 150\text{ V}$ , $I_B = 0$ )<br>2N3583,2N6420<br>2N3584,2N6421<br>2N3585,2N6422<br>2N4240,2N6423  | $I_{CEO}$     |                          | .10<br>5.0<br>5.0<br>5.0                             | mA |
| Collector Cutoff Current<br>( $V_{CE} = 225\text{ V}$ , $V_{BE(off)} = 1.5\text{ V}$ )<br>( $V_{CE} = 340\text{ V}$ , $V_{BE(off)} = 1.5\text{ V}$ )<br>( $V_{CE} = 450\text{ V}$ , $V_{BE(off)} = 1.5\text{ V}$ )<br>2N3583,2N6420<br>2N3584,2N6421<br>2N3585,2N6422<br>2N4240,2N6423<br>( $V_{CE} = 225\text{ V}$ , $V_{BE(off)} = 1.5\text{ V}$ , $T_C = 150^\circ\text{C}$ )<br>( $V_{CE} = 300\text{ V}$ , $V_{BE(off)} = 1.5\text{ V}$ , $T_C = 150^\circ\text{C}$ )<br>2N3583,2N6420<br>2N3584,2N6421<br>2N3585,2N6422<br>2N4240,2N6423 | $I_{CEX}$     |                          | 1.0<br>1.0<br>1.0<br>2.0<br>3.0<br>3.0<br>3.0<br>5.0 | mA |
| Emitter Cutoff Current<br>( $V_{EB} = 6.0\text{ V}$ , $I_C = 0$ )<br>2N3583,2N6420<br>2N3584,2N6421<br>2N3585,2N6422<br>2N4240,2N6423  | $I_{EBO}$     |                          | 5.0<br>0.5<br>0.5<br>0.5                             | mA |


## ON CHARACTERISTICS (1)

|   |               |  |                               |   |
|---|---------------|--|-------------------------------|---|
| DC Current Gain<br>( $I_C = 0.1\text{ A}$ , $V_{CE} = 10\text{ V}$ )<br>( $I_C = 0.5\text{ A}$ , $V_{CE} = 10\text{ V}$ )<br>( $I_C = 0.75\text{ A}$ , $V_{CE} = 2.0\text{ V}$ )<br>( $I_C = 0.75\text{ A}$ , $V_{CE} = 10\text{ V}$ )<br>( $I_C = 1.0\text{ A}$ , $V_{CE} = 2.0\text{ V}$ )<br>All devices<br>2N3583,2N6420<br>2N4240,2N6423<br>2N4240,2N6423<br>2N3584,2N6421<br>2N3585,2N6422<br>2N3583,2N6420<br>2N3C84,2N6421<br>2N3585,2N6422 | hFE           | 40<br>40<br>10<br>30<br>8.0<br>8.0<br>10<br>25<br>25 | 200<br>100<br>150<br>80<br>80 |   |
| Collector - Emitter Saturation Voltage<br>( $I_C = 0.75\text{ A}$ , $I_B = 75\text{ mA}$ )<br>( $I_C = 1.0\text{ A}$ , $I_B = 125\text{ mA}$ )<br>2N4240,2N6423<br>2N3583,2N6420<br>2N3584,2N6421<br>2N3585,2N6422  | $V_{CE(sat)}$ |  | 1.0<br>5.0<br>0.75<br>0.75    | V |
| Base - Emitter Saturation Voltage<br>( $I_C = 0.75\text{ A}$ , $I_B = 75\text{ mA}$ )<br>( $I_C = 1.0\text{ A}$ , $I_B = 100\text{ mA}$ )<br>2N4240,2N6423<br>2N3584,2N6421<br>2N3585,2N6422  | $V_{BE(sat)}$ |  | 1.8<br>1.4<br>1.4             | V |
| Base - Emitter On Voltage<br>( $I_C = 1.0\text{ A}$ , $V_{CE} = 10\text{ V}$ )<br>All devices   | $V_{BE(on)}$  |  | 1.4                           | V |


(1) Pulse Test: Pulse width = 300 us, Duty Cycle  $\leq$  2.0%

2N3583 thru 2N3585,2N4240


DC CURRENT GAIN



COLLECTOR SATURATION REGION




"ON" VOLTAGES




2N6420 thru 2N6423


DC CURRENT GAIN




COLLECTOR SATURATION REGION




"ON" VOLTAGES




2N3583 thru 2N3585, 2N4240  
ACTIVE REGION SAFE OPERATING AREA




2N6420 thru 2N6423  
ACTIVE REGION SAFE OPERATING AREA




TURN-ON TIME



TURN-ON TIME



TURN-OFF TIME



TURN-OFF TIME

