



2.5" SSD

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



Key Features

- MCU-based Power Loss Protection Design*
- Self-Encrypting Drive (SED) with AES 256-bit Encryption, TCG OPAL 2.0*
- NSA-compliant Secure Erase*
- MIL-STD-810G standards*

* May vary by product and project support

ATP's shock/vibration-resistant industrial 2.5" SSDs are encased in durable enclosures for outstanding performance in challenging environments. The convenient 2.5" form factor and SATA III interface allow easy integration into SATA-based systems, while unique ATP technologies ensure extended endurance for long years of dependable use.

Power Loss Protection Design technology options combines hardware and/or firmware solutions to ensure that data is preserved and protected during a sudden power failure. The MCU design also protects the storage device from damage by allowing the power loss protection (PLP) to intelligently manage power challenges such as inrush current, input overvoltage, incorrect cache flushing and more.

ATP's 2.5" SSDs comply with US National Security Agency (NSA) and MIL-STD-810G standards. They support the S.M.A.R.T. ATA feature set and Advanced Wear Leveling algorithm for enhanced endurance.

Technologies & Add-On Services	S.M.A.R.T.	Hardware-based Power Loss Protection	AutoRefresh	Advanced Wear Leveling	Dynamic Data Refresh	Secure Erase	TCG Opal 2.0	Industrial Temperature	Anti-Sulfur Resistors	Conformal Coating
Premium	○	○	○	○	○	▲	○	○	▲	▲
Superior	○	○	○	○	○	▲	○	▲	▲	▲
Value	○	—	○	○	○	—	—	—	—	—

▲: Customization option available on a project basis.

Specifications

2.5" SSD					
Product Line	Premium			Superior	
	A800Pi	A750Pi	A700Pi	A650Si	A650Sc
Interface	SATA III 6 Gb/s				
Flash Type	SLC	3D TLC (pSLC mode)		3D TLC	
Form Factor	2.5"				
Operating Temperature (Tcase) ¹	-40°C to 85°C			0°C to 70°C	
Power Loss Protection Options	Hardware + Firmware Based				
Optional SED Features	-			AES 256-bit Encryption, TCG Opal 2.0	
Capacity	8 GB to 256 GB	80 GB to 640 GB		120 GB to 1,920 GB	
Performance					
Sequential Read (MB/s) up to	520	560		560	
Sequential Write (MB/s) up to	420	520		520	
Random Reads IOPS (4K, QD32) up to	76,000	90,000		100,000	
Random Writes IOPS (4K, QD32) up to	74,000	88,000		91,000	
Endurance and Reliability					
Endurance (TBW) ² up to	21,333 TB	38,400 TB	25,600 TB	9,310 TB	
Reliability MTBF @ 25°C	>2,000,000 hours				
Reliability Number of Insertions	10,000 minimum				
Others					
Dimensions: L x W x H (mm)	100 x 69.9 x 9.2	100 x 69.9 x 7/9.2			
Certifications	CE, FCC	CE, FCC, BSMI, UKCA, RoHS, REACH			
Warranty	5 years			2 years	

2.5" SSD			
Product Line	Superior		Value
	A600Si	A600Sc	A600Vc
Interface	SATA III 6 Gb/s		
Flash Type	3D TLC		
Form Factor	2.5"		
Operating Temperature (Tcase) ¹	-40°C to 85°C	0°C to 70°C	0°C to 70°C
Power Loss Protection Options	Hardware + Firmware Based		Firmware Based
Optional SED Features	AES 256-bit Encryption, TCG Opal 2.0		-
Capacity	120 GB to 1,920 GB		32 GB to 1 TB
Performance			
Sequential Read (MB/s) up to	560		560
Sequential Write (MB/s) up to	520		525
Random Reads IOPS (4K, QD32) up to	100,000		72,000
Performance Random Writes IOPS (4K, QD32) up to	91,000		85,000
Endurance and Reliability			
Endurance (TBW) ² up to	5,585 TB		2,792 TB
Reliability MTBF @ 25°C	>2,000,000 hours		
Reliability Number of Insertions	10,000 minimum		
Others			
Dimensions: L x W x H (mm)	100 x 69.9 x 7/9.2		100 x 69.9 x 7
Certifications	CE, FCC, BSMI, UKCA, RoHS, REACH		
Warranty	2 years		

1 Case Temperature, the composite temperature as indicated by SMART temperature attributes.

2 Under highest Sequential write value. May vary by density, configuration and applications.

Hot Items Ordering Information

Product Line	Capacity ₁	Operating Temperature ₂	Power Loss Protection ₃	SED ₄	P/N
A800Pi	8GB	-40°C to 85°C	Hardware + Firmware Based	-	AF8GSSCJ-VACXP
A800Pi	16GB	-40°C to 85°C	Hardware + Firmware Based	-	AF16GSSCJ-VACXP
A800Pi	32GB	-40°C to 85°C	Hardware + Firmware Based	-	AF32GSSCJ-VACXP
A800Pi	64GB	-40°C to 85°C	Hardware + Firmware Based	-	AF64GSSCJ-VACXP
A800Pi	128GB	-40°C to 85°C	Hardware + Firmware Based	-	AF128GSSCJ-VACXP
A800Pi	256GB	-40°C to 85°C	Hardware + Firmware Based	-	AF256GSSCJ-VACXP
A650Si	120GB	-40°C to 85°C	Hardware + Firmware Based	-	AF120GSTCJ-7BCIP
A650Si	240GB	-40°C to 85°C	Hardware + Firmware Based	-	AF240GSTCJ-7BCIP
A650Si	480GB	-40°C to 85°C	Hardware + Firmware Based	-	AF480GSTCJ-7BCIP
A650Si	960GB	-40°C to 85°C	Hardware + Firmware Based	-	AF960GSTCJ-7BCIP
A650Si	1.92TB	-40°C to 85°C	Hardware + Firmware Based	-	AF1T92STCJ-7BCIP
A650Sc	120GB	0°C to 70°C	Hardware + Firmware Based	-	AF120GSTCJ-7BCXP
A650Sc	240GB	0°C to 70°C	Hardware + Firmware Based	-	AF240GSTCJ-7BCXP
A650Sc	480GB	0°C to 70°C	Hardware + Firmware Based	-	AF480GSTCJ-7BCXP
A650Sc	960GB	0°C to 70°C	Hardware + Firmware Based	-	AF960GSTCJ-7BCXP
A650Sc	1.92TB	0°C to 70°C	Hardware + Firmware Based	-	AF1T92STCJ-7BCXP
A600Vc	32GB	0°C to 70°C	Firmware Based	-	AF32GSTCJ-2BAXX
A600Vc	64GB	0°C to 70°C	Firmware Based	-	AF64GSTCJ-2BAXX
A600Vc	128GB	0°C to 70°C	Firmware Based	-	AF128GSTCJ-2BAXX
A600Vc	256GB	0°C to 70°C	Firmware Based	-	AF256GSTCJ-2BAXX
A600Vc	512GB	0°C to 70°C	Firmware Based	-	AF512GSTCJ-2BAXX
A600Vc	128GB	0°C to 70°C	Firmware Based	-	AF128GSTCJ-2BBXX
A600Vc	256GB	0°C to 70°C	Firmware Based	-	AF256GSTCJ-2BBXX
A600Vc	512GB	0°C to 70°C	Firmware Based	-	AF512GSTCJ-2BBXX
A600Vc	1TB	0°C to 70°C	Firmware Based	-	AF1TSTCJ-2BBXX

1 Amount of actual usable storage that can be utilized.

2 Refers to Case Temperature range during device operation, as indicated by SMART temperature attributes.

3 Hardware + Firmware-based power loss protection design with Level 4 (data-in-flight) protection; Firmware-based power loss protection design with Level 1 (data-at-rest) protection.

4 Allows data written to and read from the SSD to be constantly and automatically encrypted and decrypted. Conforms to TCG Opal 2.0 and uses AES 256-bit HW encryption.

Product spec and its related information are subject to change without advance notice.
Please refer to www.atpinc.com for latest information

v1.1 202205

© Copyright 2022 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
sales@cn.atpinc.com