


SERIES: CP40 | **DESCRIPTION:** PELTIER MODULE**FEATURES**

- arcTEC™ structure on select models
- solid state device
- precise temperature control
- quiet operation

**MODEL**

| | input voltage ¹ | input current ² | internal resistance ³ | output Qmax ⁴ | | output ΔTmax ⁵ | |
|------------------------|----------------------------|----------------------------|----------------------------------|-----------------------------|-----------------------------|------------------------------|------------------------------|
| | max [Vdc] | max [A] | typ [Ω±10%] | T _h =27°C [W] | T _h =50°C [W] | T _h =27°C [°C] | T _h =50°C [°C] |
| CP40136 | 3.8 | 4.0 | 0.80 | 8.1 | 9.0 | 66 | 72 |
| CP40236 | 8.6 | 4.0 | 2.0 | 18.7 | 21.8 | 66 | 72 |
| CP40336 | 15.4 | 4.0 | 3.5 | 33.4 | 37.3 | 66 | 72 |
| CP40147 | 2.1 | 4.0 | 0.42 | 4.2 | 4.6 | 68 | 75 |
| CP40247 | 3.8 | 4.0 | 0.77 | 7.5 | 8.3 | 68 | 75 |
| CP402533 ⁶ | 15.4 | 4.0 | 2.88 | 35.2 | 39.0 | 68 | 75 |
| CP40301547 | 4.2 | 4.0 | 0.87 | 8.4 | 9.2 | 68 | 75 |
| CP40347 ⁶ | 8.6 | 4.0 | 1.76 | 19.6 | 21.6 | 70 | 77 |
| CP40439 ⁶ | 19.5 | 4.0 | 4.18 | 45.0 | 49.5 | 68 | 75 |
| CP404046 ⁶ | 24.1 | 4.0 | 4.94 | 55.7 | 61.2 | 68 | 75 |
| CP40447 ⁶ | 15.4 | 4.0 | 3.15 | 32.0 | 35.2 | 70 | 77 |
| CP4055485 ⁶ | 29.8 | 4.0 | 5.97 | 63.0 | 69.0 | 70 | 77 |


Notes: 1. Maximum voltage at ΔT max and T_h=27°C
 2. Maximum current to achieve ΔT max
 3. Measured by AC 4-terminal method at 25°C
 4. Maximum heat absorbed at cold side occurs at I_{max}, V_{max}, and ΔT=0°C
 5. Maximum temperature difference occurs at I_{max}, V_{max}, and Q=0W (ΔT max measured in a vacuum at 1.3 Pa)
 6. Designed with arcTEC™ structure.

SPECIFICATIONS


| parameter | conditions/description | min | typ | max | units |
|----------------------------|--|-----|-----|-----|-------|
| solder melting temperature | connection between thermoelectric pairs | | | | |
| | CP40347, CP40447, CP40147, CP40247, CP402533 | 235 | | | °C |
| | CP40301547, CP404046, CP40439, CP4055485 | 138 | | | °C |
| assembly compression | | | | 1 | MPa |
| RoHS | yes | | | | |

MECHANICAL DRAWING

units: mm




| | MATERIAL | PLATING |
|----------------------------------|---|---------|
| ceramic plate | 96% AL ₂ O ₃ | |
| wire leads [3.3 & 3.6 mm models] | 22 AWG | tin |
| wire leads [all other models] | mod- 20 AWG | tin |
| sealer | silicon rubber 703 RTV (between cold and hot side plates) | |
| joint cover | silicon rubber 703 RTV | |
| marking | P/N & S/N printed on cold side surface | |




| MODEL NO. | LENGTH [mm] | WIDTH [mm] | THICKNESS [mm] |
|------------------------|-------------|------------|----------------|
| CP40136 | 15 ±0.3 | 15 ±0.3 | 3.6 ±0.1 |
| CP40236 | 20 ±0.3 | 20 ±0.3 | 3.6 ±0.1 |
| CP40336 | 30 ±0.3 | 30 ±0.3 | 3.6 ±0.1 |
| CP40147 | 15 ±0.3 | 15 ±0.3 | 4.6 ±0.1 |
| CP40247 | 20 ±0.3 | 20 ±0.3 | 4.6 ±0.1 |
| CP402533 ¹ | 25 ±0.3 | 25 ±0.3 | 3.3 ±0.1 |
| CP40301547 | 30 ±0.3 | 15 ±0.3 | 4.6 ±0.1 |
| CP40347 ¹ | 30 ±0.3 | 30 ±0.3 | 4.6 ±0.1 |
| CP40439 ¹ | 40 ±0.3 | 40 ±0.3 | 3.9 ±0.1 |
| CP404046 | 40 ±0.3 | 40 ±0.3 | 4.6 ±0.1 |
| CP40447 ¹ | 40 ±0.3 | 40 ±0.3 | 4.6 ±0.1 |
| CP4055485 ¹ | 55 ±0.3 | 55 ±0.3 | 4.85 ±0.1 |

Notes: 1. Wire lead strip length on models CP40347, CP40447, CP40439, CP402533, & CP4055485 is 10 ±3.0 mm.


CP40136 PERFORMANCE (Th=27°C)




CP40136 PERFORMANCE (Th=50°C)




CP40236 PERFORMANCE (Th=27°C)




CP40236 PERFORMANCE (Th=50°C)




CP40336 PERFORMANCE (Th=27°C)




CP40336 PERFORMANCE (Th=50°C)




CP40147 PERFORMANCE (Th=27°C)




CP40147 PERFORMANCE (Th=50°C)




CP40247 PERFORMANCE (Th=27°C)




CP40247 PERFORMANCE (Th=50°C)




CP402533 PERFORMANCE (Th=27°C)




CP402533 PERFORMANCE (Th=50°C)




CP40301547 PERFORMANCE (Th=27°C)




CP40301547 PERFORMANCE (Th=50°C)




CP40347 PERFORMANCE (Th=27°C)




CP40347 PERFORMANCE (Th=50°C)




CP40439 PERFORMANCE (Th=27°C)




CP40439 PERFORMANCE (Th=50°C)




CP404046 PERFORMANCE (Th=27°C)




CP404046 PERFORMANCE (Th=50°C)




CP40447 PERFORMANCE (Th=27°C)




CP40447 PERFORMANCE (Th=50°C)



CP4055485 PERFORMANCE (Th=27°C)



CP4055485 PERFORMANCE (Th=50°C)



REVISION HISTORY

| rev. | description | date |
|------|--|------------|
| 1.0 | initial release | 09/03/2009 |
| 1.01 | applied new template | 05/08/2012 |
| 1.02 | added new models | 09/08/2016 |
| 1.03 | changed models CP40347 & CP40447 to arcTEC™ structure | 12/01/2017 |
| 1.04 | changed thickness of CP40147, CP40247, CP40301547 models | 09/19/2018 |
| 1.05 | added models CP40439, CP404046, CP4055485, brand update | 10/18/2019 |
| 1.06 | added model CP402533 | 11/17/2020 |
| 1.07 | logo, datasheet style update | 08/05/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com