

Specification Sheet

Part Number: 156-00089

Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.

Fir tree provides low insertion effort yet demonstrates high extraction resistance.

Disc feature prevents rattling in high-vibration applications and protects against debris ingress.



2-Piece Cable Tie/Fir Tree Mount, 6.0"L, 0.38 - 0.39" Mounting Hole, 30lb, PA66HIRHS, Black, 500/pkg

Article Number 156-00089

Type T30RFT10

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description 2-Piece Cable Tie/Fir Tree Mount, 6.0"L, 0.38 - 0.39" Mounting Hole, 30lb, PA66HIRHS, Black, 500/pkg

Global Part Name T30RFT10-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 30.0

Minimum Tensile Strength (Metric) 135

Length L (Imperial) 6.0

Length L (Metric) 148.0

Fixation Method Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14

Width W (Metric) 3.6

Bundle Diameter Min (Imperial) 0.16

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 1.4

Bundle Diameter Max (Metric) 35.0

Height H (Imperial) .04

| | |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------|
| Height H (Metric) | 1.10 |
| Panel Thickness Min (Imperial) | 0.031 |
| Panel Thickness Max (Imperial) | 0.197 |
| Panel Thickness Min (Metric) | 0.8 |
| Panel Thickness Max (Metric) | 5.0 |
| Mounting Hole Diameter D (Imperial) | 0.38 - 0.39 |
| Mounting Hole Diameter D (Metric) | 9.7 - 10.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.38 |
| Mounting Hole Diameter D Max (Imperial) | 0.39 |
| Mounting Hole Diameter D Max (Metric) | 10.0 |
| Disc Diameter (Metric) | 18.0 |
| Disc Diameter (Imperial) | 0.7 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS PA66HS |
| Flammability | UL 94 V-2 |

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988