

# 3M™ Trizact™ Lapping Film Aluminum Oxide 269XA

## Product Description

A microreplicated abrasive film product using tightly graded aluminum oxide minerals coated onto a polyester film backing. Available with PSA (Pressure Sensitive Adhesive).

## Applications

- Flat lapping
- Cullet removal
- Glass, metal, plastic processing and repair

## Key Features

- Long life
- Produces excellent surface finish
- Consistent cut rates
- Reduces overall process time
- Produces high yields
- Non-slurry processing

## Product I.D.

Product ID (plain back)	Product ID (with PSA backing)	Backing
269XA	269XA	3 mil

## Converted Forms

Sheets, Discs and Rolls.  
Maximum width 25".

## Backing

Polyester Film  
Nominal thickness: 3 mil.

## Mineral Size Grading Chart

Micron Grade (nominal)	Color
5	Orange
10	Blue
20	Pink
35	Green

## Storage and Shelf Life

Recommended Storage Conditions:  
50-90°F at 30-70% relative humidity.

It is recommended that product be used within 24 months of purchase.



# 3M™ Trizact™ Lapping Film Aluminum Oxide 269XA

## Certification/Recognition

**MSDS:** 3M has prepared an MSDS for this product, although it is not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the 3M directions for use, the product should not present a health and safety hazard. However, use or processing of the product in a manner not in accordance with the directions for use may affect its performance and present potential health and safety hazards.

**TSCA:** This product is defined as an article under the Toxic Substances Control Act and therefore, it is exempt from inventory listing requirements.

**RoHs Complaint/REACH Compliant:** This product complies with the European Union's "Restriction of Hazardous Substances" (RoHs) initiative and with European REACH regulations 2002/95/EC and 2005/618/EC.

## For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-866-599-4227.

Address correspondence to: 3M, Electronics Markets Materials Division, 3M Center, Building 225-3S-06, St. Paul, MN 55144-1000.

Our fax number is 651-778-4244 or 1-877-369-2923.

In Canada, phone: 1-800-364-3577.

In Puerto Rico, phone: 1-787-750-3000.

In Mexico, phone: 52-70-04-00.

## Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

## Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



### Electronics Markets Materials Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
1-866-599-4227 phone  
651-778-4244 fax  
www.3M.com/electronics

3M and Trizact are trademarks  
of 3M Company.  
Please recycle. Printed in U.S.A.  
©3M 2010. All rights reserved.  
60-5002-0468-4

