NOTES: UNLESS OTHERWISE SPECIFIED

1. P/N: 9476COLOR

HOUSING: POLYAMIDE/POLYOXYMETHYLENE

AVAILABLE IN BLK, RED, YEL, GRN, BLU, WTE


FRAME: NICKEL PLATED BRASS CONTACT: NICKEL PLATED CuBe

2. P/N: W-200/COLOR
22AWG 65X40 TINNED COPPER
0.070 [1.78] O.D. PVC INSULATION
AVAILABLE IN TEN COLORS.

3. PERFORMANCE

MAXIMUM CURRENT: 2.5 AMPS

MAXIMUM VOLTAGE: < 33VAC < 70VDC. MAXIMUM TEMPERATURE: 221°F (105°C)



		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES	CONTRACT NO.  APPROVALS	DATE	E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.
		± .XX ± ± .XXX ±	DRAWN R.L.	10/18	DESCRIPTION
		MATERIAL SEE NOTE.	APPROVED BY		2MM SIK BAN PLUG (9476) JUMPER
					(3173) 33111 =11
		FINISH			SIZE CODE IDENT NO. DRAWING NO. REV.
NEXT ASSY	USED ON	-SEE NOTE.			B   <b>08505</b>   9922
APPLICATION		DO NOT SCALE DRAWING			SCALE 1:1 SHEET 1 OF 1

LTR

REVISIONS

DESCRIPTION

APPROVED

DATE