



3M™ Dynatel™ 12-watt Transmitter 2200M Series

A newer, higher powered transmitter is the latest addition to the 3M Dynatel products family. This portable 12-watt output transmitter is compatible with existing M-series receivers and provides the maximum allowed induction power. The 12-watt transmitter can be powered by six C-size alkaline batteries, the rechargeable battery pack, or 12V external power supply.

A Reputation of Excellence

When you choose a quality 3M™ Dynatel™ Locator, you get outstanding performance and reliability, along with 24/7 technical support and a service center dedicated to excellence. Our service center provides calibration, repair, upgrades and modifications for safety, performance and reliability.

Product Features

- Maximum allowed output power
- Four active frequencies, direct connect & Dynacoupler
- Three induction frequencies
- All frequency mode in direct connect
- Automatic impedance matching
- Ohm meter with high voltage detection
- Rugged, industrial temperature range
- 240VAC output protection
- Standard alkaline (c-cell) batteries
- Rechargeable battery kit



3M™ Dynatel™ 12-watt Transmitter 2200M Series



3M™ Dynatel™ 12-watt Transmitter 2200M Series

Ordering Information

		Cable/Pipe Locate	Earth Return Fault Locate	Electronic Marker Locate	US Receiver	International Receiver	US 12W Transmitter	International 12W Transmitter	Direct Connect Cable—small clips	Direct Connect Cable—large clips	3" Coupler	Coupler Cable	A Frame	A Frame Cable	Ground Rod	2200RB Rechargeable Battery	Cigarette Lighter Adapter Cable	2200M Carrying Bag
US Versions Locator Kits																		
80-6113-3107-7	2220M-UCU12W/RT	■			■		■		■	■	■	■			■	■	■	■
80-6113-3041-8	2250M-UCU12W/RT	■			■		■		■	■	■	■			■	■	■	■
80-6113-3039-2	2250M-ID/UCU12W-RT	■		■	■		■		■	■	■	■			■	■	■	■
80-6113-3040-0	2250M-ID/UW12W-RT	■		■	■		■		■	■	■	■			■	■	■	■
80-6113-3046-7	2273M-UCU12W/RT	■	■		■		■		■	■	■	■	■	■	■	■	■	■
80-6113-3044-2	2273M-ID/UCU12W-RT	■	■	■	■		■		■	■	■	■	■	■	■	■	■	■
80-6113-3045-9	2273M-ID/UW12W-RT	■	■	■	■		■		■	■	■	■	■	■	■	■	■	■
International Versions Locator Kits																		
80-6113-3207-5	2220M-ECU12W/RT	■				■		■	■	■	■	■			■	■	■	■
80-6113-3037-6	2250M-ECU12W/RT	■				■		■	■	■	■	■			■	■	■	■
80-6113-3038-4	2250M-ID/ECU12W-RT	■		■		■		■	■	■	■	■			■	■	■	■
80-6113-3042-6	2273M-ECU12W/RT	■	■			■		■	■	■	■	■	■	■	■	■	■	■
80-6113-3043-4	2273M-ID/ECU12W-RT	■	■	■		■		■	■	■	■	■	■	■	■	■	■	■
US Versions (Transmitter Only)																		
80-6113-3108-5	2250M-U12WT						■								■	■	■	
80-6113-3032-7	2273M-U12WT						■								■	■	■	
International Versions (Transmitter Only)																		
80-6113-3109-3	2250M-E12WT							■	■	■					■	■	■	
80-6113-3033-5	2273M-E12WT							■	■	■					■	■	■	

12-watt Transmitter Specifications

Trace mode frequencies	
2220M	8 kHz, 82 kHz
2250M/2273M	577 Hz, 8 kHz, 33 kHz, 200 kHz
2250ME/2273ME (International)	577 Hz, 8 kHz, 33 kHz, 133 kHz
Fault mode frequencies	
	10/20 Hz -fault
	577 Hz / 33 kHz -trace
Induction mode frequencies	
2220M	8 kHz, 82 kHz
2250M/2273M	8 kHz, 33 kHz, 200 kHz
2250ME/2273ME (International)	8 kHz, 33 kHz, 133 kHz
Pulsing tone frequencies	
2220M	n/a
2250M/2273M	577 Hz, 200 kHz
2250ME/2273ME (International)	577 Hz, 133 kHz
Output power (maximum)	
	3 watt maximum
	12 watt w/external DC source (varies by frequency)
Output voltage (maximum)	
	70 Vrms
Output Protection	
	240 Vrms
Weight w/batteries (alkaline)	
	5.2 lbs (2.4 kg)
Battery Quantity and size	
	6 "C" alkaline (LR14)
Battery Life	
	40 hours typical (normal output level)
	10 hours typical (high output level)
	Rechargeable battery will extend operation time by 40%
External DC power	
	9–18 V DC
Standard	
	IP54
Regulatory	
	CE, FCC
Operating Temperature	
	-4°F to 122°F (-20°C to 50°C)
Storage Temperature	
	-4°F to 158°F (-20°C to 70°C)



3M™ Rechargeable Battery 2200RB

3M and Dynatel are trademarks of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 12 months from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether indirect, special, incidental or consequential regardless of the legal theory asserted.**



Track and Trace Solutions

6801 River Place Blvd.
Austin, TX 78726-9000
800/426 8688
Fax 800/626 0329
www.3M.com/dynatel

Please recycle. Printed in USA.
© 3M 2009. All rights reserved.
80-6113-2854-5