

Insulated cross-connector, No. of poles: 20, Mounting type: Plug in, Width: 159.4 mm, Colour: Blue

RAL: Ähnlich 5005

Business data Article number 27161.5 PQI 6/20 BU Article name 4044211234362 GTIN (EAN) Packaging unit 50 PC Quantity unit Weight per piece (not including packaging) 33.14 g Weight per piece (including packaging) 33.34 g Unit of weight G Customs number 85389099 Country of origin DE **Prio-Article** 27161.9 Product description Insulated cross-connector



Technical data

Length4 mmWidth159.4 mmHeight22.5 mmPitch size8.1 mmRatings800 VRated current41 ACurrent load, max.41 ARated cross-section6 mm²Contamination degree3Connection data7No. of poles20Materials1Insulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min.40 °CWorking temperature, max.120 °CFurther technical data✓Mounting typePlug inInsulation available✓Jouch protection is available✓Vorking temperature, max20Environmental Product Compliance✓REACH ConformyesREACH ConformyesREACH Candidate Substance NoteNoRoHS Conformyes	Dimensions	
Height22.5 mmPitch size8.1 mmRatingsMax. voltageMax. voltage800 VRated current41 ACurrent load, max.41 ARated cross-section6 mm²Contamination degree3Connection data20No. of poles20MaterialsInsulation housingInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical data✓Mounting typePlug inInsulation available✓Vul protection is available✓Vul protection is available✓REACH ConformyesREACH Reference date2022-06-10REACH Reference date2022-06-10REACH Candidate Substance NoteNo	Length	4 mm
Pitch size 8.1 mm Ratings 800 V Rated current 41 A Current load, max. 41 A Rated cross-section 6 mm² Contamination degree 3 Connection data 0 No. of poles 20 Materials 1 Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data 120 °C Mounting type Plug in Insulation available √ Touch protection is available √ Number of bridged terminals 20 Environmental Product Compliance 20 REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Width	159.4 mm
Ratings Max. voltage 800 V Rated current 41 A Current load, max. 41 A Rated cross-section 6 mm² Contamination degree 3 Connection data No. of poles 20 Materials 20 Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data Mounting type Plug in Insulation available √ Touch protection is available √ Number of bridged terminals 20 Environmental Product Compliance REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Height	22.5 mm
Max. voltage 800 V Rated current 41 A Current load, max. 41 A Rated corss-section 6 mm² Contamination degree 3 Connection data 20 Materials 20 Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data	Pitch size	8.1 mm
Rated current 41 A Current load, max. 41 A Rated cross-section 6 mm² Contarnination degree 3 Connection data 20 Materials 20 Insulation housing Polyamide 6.6 Flarmability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data V Mounting type Plug in Insulation available √ Touch protection is available √ Number of bridged terminals 20 Environmental Product Compliance 20 REACH Conform yes REACH Conforder No	Ratings	
Current load, max. 41 A Rated cross-section 6 mm² Contamination degree 3 Connection data	Max. voltage	800 V
Rated cross-section6 mm²Contamination degree3Connection dataNo. of poles20MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product Compliance20REACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Rated current	41 A
Contamination degree3Connection dataNo. of poles20MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Current load, max.	41 A
Connection data No. of poles 20 Materials Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data	Rated cross-section	6 mm ²
No. of poles 20 Materials Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 20 Environmental Product Compliance REACH Conform REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Contamination degree	3
Materials Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data Plug in Mounting type Plug in Insulation available ✓ Yourking temperature, min.sevent 20 Environmental Product Compliance Ves REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Connection data	
Insulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	No. of poles	20
Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 20 Environmental Product Compliance yes REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Materials	
Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Insulation housing	Polyamide 6.6
Working temperature, max.120 °CFurther technical dataPlug inMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Flammability class UL 94	V-0
Further technical data Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 20 Environmental Product Compliance Yes REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Working temperature, min.	-40 °C
Mounting typePlug inInsulation available✓Insulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Working temperature, max.	120 °C
Insulation available✓Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Further technical data	
Touch protection is available✓Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Mounting type	Plug in
Number of bridged terminals20Environmental Product ComplianceREACH ConformyesREACH Reference date2022-06-10REACH Candidate Substance NoteNo	Insulation available	\checkmark
Environmental Product Compliance REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Touch protection is available	\checkmark
REACH Conform yes REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Number of bridged terminals	20
REACH Reference date 2022-06-10 REACH Candidate Substance Note No	Environmental Product Compliance	
REACH Candidate Substance Note No	REACH Conform	yes
	REACH Reference date	2022-06-10
RoHS Conform yes	REACH Candidate Substance Note	No
	RoHS Conform	yes

Media



ZCONTACLIP

Accessories

##INVERSE##CONTA-CONNECT

	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Green-yellow				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27021.2	PSL 6/3A GNYE	4044211223960	50 ST	
	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Green-yellow				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27023.2	PSL 6/4A GNYE	4044211224004	50 ST	
	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Green-yellow				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27019.2	PSL 6/2A GNYE	4044211223922	50 ST	
	Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Grey				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27018.6	PRK 6/2A GR	4044211223915	50	