


Protective film 10" front Type 4, edge adhesive, reflection shield matte,
Further information, quantity and content: See technical data



Figure similar

| General information | |
|---|--|
| Product type designation | Protective film 10" front, type 4 |
| Installation type/mounting | |
| Mounting in portrait format possible | Yes |
| Mounting in landscape format possible | Yes |
| Standards, approvals, certificates | |
| CE mark | No; No CE marking obligation |
| REACH | Yes; Tested |
| RoHS conformity | Yes; unnecessary |
| Ambient conditions | |
| Suited for indoor use | Yes |
| Suited for outdoor use | No; possible under certain conditions |
| Ambient temperature during operation | |
| • min. | 0 °C |
| • max. | 55 °C |
| Ambient temperature during storage/transportation | |
| • min. | -20 °C |
| • max. | 60 °C |
| Relative humidity | |
| • Operation, max. | 50 % |
| Mechanics/material | |
| Material | Autoflex EBA 130 |
| • Plastic | Yes; Non-reflecting, matte, can be removed without residue |
| • PET | Yes; Non-antistatic, non-reflecting |
| Enclosure material (front) | Scratch resistance 2-3H |
| Dimensions | |
| Width | 311.5 mm |
| Height | 200.5 mm |
| Thickness | 0.225 mm; Corners radius 7.4 mm |
| Weights | |
| Weight (without packaging) | 16 g; Per unit |
| Weight (with packaging) | 1 800 g; Complete set |
| Scope of supply | |
| Delivery quantity in pieces | 5; Units per set |
| Components included | Without additional accessories |
| Other | |
| printable with laser printer | No; suitable for screen printing or UV printing |

| | |
|---|--|
| Merchandise | Yes; Autoflex EBA 130 |
| Manufacturer name | Kolb-Siebdruck GmbH & Co. KG |
| Manufacturer's address | Kolb-Siebdruck GmbH & Co. KG |
| contacting the manufacturer | Email: design@kolb-siebdruck.de |
| Target devices | Tablet PC with/without touch screen |
| Note: | Edge-adhesive film, can be trimmed to a limited extent, printable, observe target device manual before attaching, high suitability for resistive touch systems, limited suitability for glass fronts |
| Usable in the following products | |
| • Product 1 | 6AV7880-* |
| last modified: | 8/24/2021  |