



TapeCase Ltd.
1982 Lunt Ave Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Double Coated Vinyl Foam Tape VF Series

PRODUCT DESCRIPTION:

Tape VF32 1/32 in. (0.8 mm) Double Coated Vinyl Foam Tape
Tape VF16 1/16 in. (1.6 mm) Double Coated Vinyl Foam Tape
Tape VF08 1/8 in. (3.2 mm) Double Coated Vinyl Foam Tape

APPLICATIONS:

General purpose mounting and joining. Surfaces and conditions for removal should be tested by the user to determine fitness for the user's particular purpose. The high degree of conformability of these tapes make them ideal for joining many rough irregular surfaces, and the closed-cell foam can make good water and air seals in certain applications.

PHYSICAL PROPERTIES:

Adhesive Type	High Tack Acrylic
Adhesive Carrier	Closed Cell Polyvinyl Chloride Foam
Density	20 lb/ft ³
Temperature Resistance	up to 150°F
Tensile Strength	60 psi
Water and Humidity Resistance	Excellent
Shelf Life	18 months from DOM

COLORS AVAILABLE: White and Black. Black only in 1/8" thickness

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.