

Master cable ring - SACB-16X0,5/3X1,0-50 PUR SH - 1539156

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Master cable ring, For use in Distributor boxes, PUR/PVC, Cable length: 50 m, Shielding: Yes



Key commercial data

| | |
|--------------------------------------|-------------|
| Packing unit | 1 PCE |
| Weight per Piece (excluding packing) | 11613.0 GRM |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

General

| | |
|---------------|-------|
| Rated voltage | 300 V |
|---------------|-------|

Master cable data/connection data

| | |
|--|--|
| Length of cable | 50 m |
| Cable type | Master cable suitable for flexible cable conduit |
| Tightening torque slot sensor/actuator cable | 0.4 Nm |

Cable

| | |
|-------------------------------------|--|
| Cable type | PUR/PVC shielded, black |
| Cable type (abbreviation) | PUR |
| Cable abbreviation | LiYY11Y-HF |
| Conductor cross section | 16x 0.5 mm ² (signal line) 3x 1 mm ² (Power supply) |
| AWG signal line | 20 |
| AWG power supply | 17 |
| Conductor structure signal line | 64x 0.10 mm |
| Conductor structure, voltage supply | 128x 0.10 mm |

Master cable ring - SACB-16X0,5/3X1,0-50 PUR SH - 1539156

Technical data

Cable

| | |
|---|---|
| Overall twist | Wires twisted in layers |
| Shielding | Tinned copper braided shield |
| External sheath, color | deep black RAL 9005 |
| External cable diameter D | 11.6 mm ±0.3 mm |
| Number of bending cycles | 1500000 |
| Minimum bending radius, drag chain applications | 10 x D |
| Traversing path | 2 m |
| Traversing rate | 2 m/s |
| Outer sheath, material | PUR |
| Material conductor insulation | PVC |
| Conductor material | Bare Cu litz wires |
| Nominal voltage, cable | 300 V |
| Test voltage, cable | 2000 V |
| Special properties | Silicone-free |
| | Free of substances which would hinder coating with paint or varnish |
| Flame resistance | DIN EN 50265 |
| Resistance to oil | As per VDE 0472 Part 803 |
| Other resistance | Highly resistant to acids, alkaline solutions and solvents |
| Ambient temperature (operation) | -40 °C ... 90 °C (cable, fixed installation) |
| | -5 °C ... 80 °C (cable, flexible installation) |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |
| eCl@ss 8.0 | 27449001 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000200 |
| ETIM 3.0 | EC001856 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

Master cable ring - SACB-16X0,5/3X1,0-50 PUR SH - 1539156

Classifications

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 31261501 |

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details



Accessories

Accessories

Stripping tool

Stripping tool - WIREFOX-D 13 - 1212162



Stripping tool, for stripping installation lines of \varnothing 8 - 13 mm , e.g. NYM 3 x 1.5 mm² to 5 x 2.5 mm², single line stripping 0.2 mm² - 4 mm² , with longitudinal cut blade and sliding knife

Master cable ring - SACB-16X0,5/3X1,0-50 PUR SH - 1539156

Accessories

Stripping tool - WIREFOX-D 40 - 1212161



Stripping tool, for stripping cables of 4.5 mm - 40 mm-Ø, insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts


Stripping tool - WIREFOX 4 - 1212156



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Drawings

Cable cross section



PUR/PVC shielded, black [PUR]