

Specification Sheet

Part Number: 151-02567

Easy to install, remove and reposition with just a quarter-turn – no tools necessary.

Multi-directional cable tie slot allows for routing a bundle parallel to or perpendicular to the frame.

Low profile is ideal for cramped spaces.

Designed to fit an 80/20 profile with a T-slot of 8 mm (0.32") and external dimensions of 40 mm (1.5").



Aluminum Frame Mount for 1.5" Frame, 2.5 - 3.0mm Panel Thickness, PA66MP+, Blue, 100/bag

Article Number 151-02567

Type MCAFLM30-1

Color Blue (BU)

Quantity Per bag

Product Description Aluminum frame mounts can be used with 20, 30 or 40 mm square frames from the major aluminum frame manufacturers. As there is no need to screw them in place, these mounts offer maximum ease of use and fast installation. The mounts contain metal particles for detection in processing plants where the potential for contamination is undesirable.

Short Description	Aluminum Frame Mount for 1.5" Frame, 2.5 - 3.0mm Panel Thickness, PA66MP+, Blue, 100/bag
Global Part Name	MCAFLM30-1-PA66MP+-BU
Length L (Imperial)	1.02
Length L (Metric)	26.0
Width W (Imperial)	0.71
Width W (Metric)	18
Cable Ties	T18 - T50
Height H (Imperial)	0.68
Height H (Metric)	17.2
Cable Tie Width Max (Imperial)	0.45
Cable Tie Width Max (Metric)	11.5
Panel Thickness Min (Imperial)	0.10
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	2.5
Panel Thickness Max (Metric)	3.0

Material	Polyamide 6.6, with metal particles (PA66MP+)
Material Shortcut	PA66MP+
Flammability	UL 94 HB
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988