36 INCHES LENGTH



Connector A 172386 N-Type Jack Straight Bulkhead - Rear Mount Brass White Bronze + Heatshrink 50 Ohm LMR-240 Continuity/Hi-Pot Connector B 102-799-48 1.0/2.3 Plug Straight Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

		Connector A		Cable			Connector B		
De Tyj Ge Bo Co Po Imj Mo Bo Bo IP	Part #:172386Description:N-Type BHD JK (Type:N-TypeGender:JackBody Type:StraightContact Type:CrimpPolarity:StandardImpedance:50 OhmMounting:Bulkhead - RearBody Material:BrassBody Finish:White BronzeIP Rating:None		Dptimized LMR240 500 Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	Cable LMR-240 LMR-240 - FEP 0.24 FEP Braid 0.24 50 Ohm None Continuity Hi-Pot 36 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating:	102-799-48 1/2.3 PLUG LMR240 Optimized 50 OHM 1.0/2.3 Plug Straight Crimp Standard 50 Ohm Cable Brass Nickel None			
Со	ontact Finish: Gold ax. Freq.: 6 GH	-	ЗНD			Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	Brass Gold 2.5 GHz 1.0/2.3 Plug Straight 0°		
Amphenol CUSTOM CABLE			THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		G Part No:	N-ST-JK/10/23-ST-PL LMR24 361			