



Poles	02	03	04	05	06	07	08	09	10	11	12	
Dim L	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76	121.92	
Dim B	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76	
TOL	±0.15		±0.25						±0.35			

- NOTES:**
- MATERIAL**
- 1. Item ⓐ Terminal (housing): Thermoplastic (UL 94V-0) Grey (RAL 7035/D)
 - 2. Item ⓑ Clamp: Brass, Ni plated
 - 3. Item ⓒ Wire guard solder pin: Copper, Tin plated
 - 4. Item ⓓ Terminal screw: Steel Zinc plating"-slot type
- ELECTRICAL** cULus IEC
- 1. Voltage rating: 300V 650V
 - 2. Current rating: 65A 57A
 - 3. Solid wire(AWG): 6-20 0.5-16mm²
 - 5. Stranded wire(AWG): 6-20 0.5-10mm²
 - 6. Torque(Lb-In): 19 1.2N.m
 - 7. Screw: M4.5
 - 8. Wire strip length: 10-11mm
 - 9. Withstanding voltage: 1.6kV 8kV
 - 10. Operating temperature: -40°C to +115°C
 - 11. Soldering temperature: 260°C ±5°C/5 Sec Δ
 - 12. Safety approval: us

RoHS compliant
Unit: mm



File No.: E3349947

Scale	Free
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

Id.	Modification	Date	Name
④	Add UL	15.03.2016	Amy
③	Change the design	19.02.2014	Amy
②	Change dimension from 1,90 to 1,70 Δ Modify Operating temperature	19.03.2009	Dean
①	Drawn	20.03.2007	Hellwig

Date	Name
Drawn 20.03.2007	Hellwig
Approved 15.03.2016	Amy

Customer-No.	ASSMANN WSW-No.	
	A-TB116-VPxx	
Drawing-No.	ASS 2179 CO	rev04
Replace	Sheet	

ASSMANN
components

1 2 3 4 5 6 7

SV1387