


Copper Conductor
42/0.16±0.1572mm

Jacket Thickness 1.14mm
Overall Diameter 3.4*6.8(±0.2)mm



(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip			Terminal Component		
Color	Component	Qty	Strip	ROJ	Color	SPT-2 18AWGX2C 105°C BLACK Length: 1829±50 mm	Strip	ROJ	Color	Component	Color	Qty
40P Black 90±5°A	LT-301(10A 125V) (NEMA1-15P)	1	7±1	15±3	Black		6±1	18±3	Black	IEC 320 C7 (LT-503B(7A 125V))	40P BK 90±5°A	1
Nickel-Plated	UL Blades	2	7±1	15±3	Black		6±1	18±3	Black	0 Type terminals	Copper	2

NOTE :

1. PLUG : LT-301(Polarity)AMERICAN TYPE
2. CONNECTOR : NA
3. CORD : SPT-2 18AWGX2C 105D BK 6FT
4. APPROVALS : UL, C-UL
5. Supplier for flexible cord : WU LI
6. Hi-Pot Test:2000v/1min<1mA>


Marking:

WU LI: (UL) 105°C SPT-2 VW-1 E94163 2*0.824mm²(18AWG)
300V WU LI CSA TYPE SPT-2 FT2 105°C LL85694
2*0.824mm²(18AWG) 300V L.F.

Modification History

NO.	DESCRIPTION	DATE

DRAWER	Aaron	DATE	22/10/11	P/N	800-1808-2-SPT2-BL-0006F-1
APPROVE		REV.	0	Dr.No.	1111002
		TOL.	±5mm		
				ALL DIMENSIONS IN mm	



比例

CnC Tech
Industrial Cable and Connector Technology