

Product information

12 42 195

KNIPEX MultiStrip 10



- Stripping without re-adjustment from 0.03 to 10.0 mm²
- recessed wire cutter
- universal blade geometry -robust and more durable
- ideal grip design with excellent haptics
- fully automatic adjustment to all single-, multi- and fine-stranded conductors with standard insulation throughout the entire capacity range from 0.03 to 10.0 mm²
- no manual fine adjustment necessary
- no damage to the conductors
- the clamping jaws made of steel hold the cable in a way that prevents slipping without damaging the remaining insulation
- with recessed wire cutter for Cu and Al conductors, stranded up to 10 mm² and single wire up to 6 mm²
- particularly smooth-running mechanics and very low weight
- replaceable blades block and length stop
- handle with soft-plastic zone for a steady grip
- body: plastic, fibreglass-reinforced
- blade: special tool steel, oil-hardened

Allgemein

Article No.	12 42 195
EAN	4003773054580
weight	136 g
Dimensions	195 x 120 x 27 mm

Technische Attribute

Stripping capacities in square millimetres	0.03 — 10.0 mm ²
AWG	32 — 7

Klassifikation

eCl@ss 5.1.4	21040302
ETIM 5.0	EC000163
ETIM 6.0	EC000163
proficl@ss 6.0	AAA002c003

technical change and errors excepted