		PROPRIETARY INFORMATION PROPRIETARY OF GLOBTEK, INC. ANY USE OF THIS DRAWING, IN WHOLE OR PROHIBITED EXCEPT AS SPECIFIED IN	REPRODUCTION, IN PART, IS HEREE	BY	REV A B C D	CORR	DESCRIPTION INITIAL RELEASE, RFS. 26492, EDD CONNECTOR DESCRIPTION, RFS. Z ECT USB TYPE END TO 12.0±0.3 mm, R I USB TYPE P1-P4 AND PIN ASSINMENT	26506, BS FS. 26584, MK	DATE 10/12/16 10/20/16 12/06/16 07/21/17	APPROVED BS BS BS BS
	P4  12±0.3  P1  USB-TYPE-A	USB00008			11	000± <u>78</u>	DC00047	11±0.5		
	2 White 3 Green (NO CONNECTE (NO CONNECTE)	5*11  ARREL CENTER ED TOGETHER ECTION TO BARREL)DC  BARREL OUTSIDE				60.0 Min	Twist Tie (2pls)	75.0 max.	Section of the Parket	000 Substance
TITLE HEAT SHRINK TU	O.D. 0.8, CC	DESCRIPTION O.D. 0.8, COLOR: BLACK			•	1;	30.0 Max  RELEASE By N.Frost at 9.4	OI am, Jul 21, 2017	H quin sallounce (Re	))) oHS
USB TYPE A PLU	CABLE UL2725 BLACK 28 AWG TWISTED PAIR + 2X 22 AWG, SHIELDED  SB TYPE A PLUG CONTACT GOLD PLATED 30u"		DASH NO.	PART NO F	REV.		DESCRIPTION			NOTES
							ABULATION BLOCK			
			TOLERANCES: DECIMALS .xx +/- 0.1 .xx x +/005  GlobTek, Inc. www.globtek.com  186 Veterans Dr. Northvale, N Tel. 201-784-1000 Fax 201.78							e, NJ 07647 01.784.0111
(s	Foot Note: Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applica- ble UL,CSA or EN Standards for proper installation instruction.	mission critical components in life support, haz- ardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	INIT.BY: BS	DATE: 10/12/16	MILLIMETERS .xx +/- 0.3 .xxx +/013	USB TYPE-A TO FEMALE BARR				
Contents of this document are subject to change without prior notice			DRAWN: NF		FSCN No.: G, CC	SIZE A				REV. D
			APRVD: MK	DATE: 10/12/16	SCALE: N	ONE	PART NO: USBA1M0LCP-	CHG(R)		SHEET 1/1