

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **0190730193**
Status: **Active**
Description: C-830-14XLBKT RAILROAD TERM TAPED

Documents:

| | |
|--------------------------------|--------------------------------------------------------------|
| 3D Model | Product Specification PS-19902-011-001 (PDF) |
| Drawing (PDF) | Product Specification PS-19902-015-001 (PDF) |
| 3D Model (PDF) | RoHS Certificate of Compliance (PDF) |

Agency Certification

| | |
|-----|---------|
| CSA | LR18689 |
| UL | E32244 |

General

| | |
|-------------------------|--------------------------|
| Product Family | Ring and Spade Terminals |
| Series | <u>19073</u> |
| Crimp Quality Equipment | Yes |
| Taxonomy | Ring and Spade Terminals |
| UPC | 800753263345 |

Physical

| | |
|--------------|---------|
| Flammability | 94V-2 |
| Net Weight | 2.480/g |

Material Info

| | |
|--------------------|---------------|
| Engineering Number | C-830-14XLBKT |
|--------------------|---------------|

Reference - Drawing Numbers

| | |
|-----------------------|------------------------------------|
| Product Specification | PS-19902-011-001, PS-19902-015-001 |
| Sales Drawing | SD-19058-006-001 |



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

Not Relevant

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

19073 Series

Application Tooling | [FAQ](#)

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

| Description | Product # |
|------------------------------------------------------------------|------------------|
| ATP Crimp Dies for the Tape Crimp Module and ATP-101 & 301 Press | <u>192880179</u> |
| Mini-Mac Pneumatic Applicator for Industrial Terminals 6-26 AWG | <u>638851500</u> |