

Wiha Easy Torque TORX® & TORXPlus® Tools With Replaceable Blades

“easy” Torque

- Audible Click At Torque
- Replaceable Blades
- +/- 10% Repeatability
- Improve Productivity
- Reduces Waste
- Controls Costs
- Save Time!

Torque accuracy of +/- 10% to 5000 cycles

Economical Torque Control for tooling assembly and repair

Reverse torque is 50% greater for easy removal using same tool

Each tool factory preset



NEW
From Wiha



SHOP

291 Easy Torque Screwdriver Handle With TORX® Blades

Easy Torque value pre-set. Release accuracy +/- 10%. Internal mechanism slips when torque value has been attained. Light weight, comfortable handle for good power transfer.

Item No.	Pre-Sets	Preset			
	Inch/lbs.	Ft./lbs.	Nm	lbs.	pkg.
291 32	T5 4.4	0.3	0.5	.26	1
291 33	T6 5.3	0.4	0.6	.26	1
291 34	T7 8.0	0.4	0.9	.26	1
291 36	T8 10.6	0.9	1.2	.26	1
291 37	T9 12.4	1.0	1.4	.26	1
291 38	T10 17.7	1.5	2.0	.26	1
291 40	T15 26.6	2.2	3.0	.26	1

* No Calibration Certificates



NEW
From Wiha

SHOP

291 90 Set 5 Pcs. Easy Torque Handle With TORX® Blade

Easy Torque value pre-set. Release accuracy +/- 10%.

Item No.	Size	mm	Size	mm	lbs.	
291 90	291 06	T7	180	291 14	T10 180	.65
	291 10	T8	180	291 18	T15 180	
	291 12	T9	180			

NEW
From Wiha



SHOP

291 Easy Torque Screwdriver Handle With TORXPlus® Blades

Easy Torque value pre-set. Release accuracy +/- 10%. Internal mechanism slips when torque value has been attained. Light weight, comfortable handle for good power transfer.

Item No.	Pre-Sets	Preset			
	Inch/lbs.	Ft./lbs.	Nm	lbs.	pkg.
291 51	IP5 4.4	0.3	0.5	.26	1
291 52	IP6 5.3	0.4	0.6	.26	1
291 53	IP7 8.0	0.7	0.9	.26	1
291 55	IP8 10.6	0.9	1.2	.26	1
291 56	IP9 12.4	1.0	1.4	.26	1
291 57	IP10 17.7	1.5	2.0	.26	1
291 59	IP15 26.6	2.2	3.0	.26	1

* No Calibration Certificates



NEW
From Wiha

SHOP

291 92 Set 5 Pcs. Easy Torque Handle With TORXPlus® Blade

Easy Torque value pre-set. Release accuracy +/- 10%.

Item No.	Size	mm	Size	mm	lbs.	
291 92	291 53	IP7	180	291 57	IP10 180	.65
	291 55	IP8	180	291 59	IP15 180	
	291 56	IP9	180			