



MICROCIRCUIT DATA SHEET

MV54ACTQ08-X REV 0A0

Original Creation Date: 03/03/97
 Last Update Date: 08/25/99
 Last Major Revision Date: 03/03/97

Quad 2-Input AND Gate

General Description

The ACTQ08 contains Four, 2- input AND gates and utilizes NSC Quiet Series technology to guarantee quiet output switching and improved dynamic threshold performance. FACT Quiet Series TM features GTO TM output control and undershoot corrector in addition to a split ground bus for superior ACMOS performance.

Industry Part Number

54ACTQ08

Prime Die

D008

NS Part Numbers

54ACTQ08E-QMLV *
 54ACTQ08ERQMLV*
 54ACTQ08J-QMLV **
 54ACTQ08JRQMLV**
 54ACTQ08W-QMLV ***
 54ACTQ08WRQMLV***

Controlling Document

5962-89547

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25 C
2	Static tests at	+125 C
3	Static tests at	-55 C
4	Dynamic tests at	+25 C
5	Dynamic tests at	+125 C
6	Dynamic tests at	-55 C
7	Functional tests at	+25 C
8A	Functional tests at	+125 C
8B	Functional tests at	-55 C
9	Switching tests at	+25 C
10	Switching tests at	+125 C
11	Switching tests at	-55 C

Features

- Guaranteed simultaneous switching noise level and dynamic threshold performance
- Improved latch-up immunity
- Minimum 4kV ESD protection
- Outputs source/sink 24 mA
- ACTQ08 has TTL-compatible inputs
- Standard Military Drawing (SMD)
 - ACTQ08: 5962- 8954702V2A*, VCA**, VDA***
 - ACTQ08: 5962R8954702V2A*, VCA**, VDA***

(Absolute Maximum Ratings)

(Note 1)

Supply Voltage (Vcc)	-0.5V to +7.0V
DC Input Diode Current (Iik)	
Vi = -0.5V	-20 mA
Vi = Vcc +0.5V	+20 mA
DC Input Voltage (Vi)	-0.5V to Vcc +0.5V
DC Output Diode Current (Iok)	
Vo = -0.5V	-20 mA
Vo = Vcc +0.5V	+20 mA
DC Output Voltage (Vo)	-0.5V to Vcc +0.5V
DC Output Source or Sink Current (Io)	±50 mA
DC Vcc or Ground Current per Output Pin (Icc or Ignd)	±50 mA
Storage Temperature (Tstg)	-65 C to +150 C
Junction Temperature (Tj)	
CDIP	175 C
Thermal Resistance, junction-to-case (jc)	See MIL-STD 1835
Maximum Power Dissipation (pd)	500 mW
Lead Temperature (soldering, 10 seconds)	+300 C

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

Recommended Operating Conditions

Supply Voltage (Vcc)	4.5V to 5.5V
Input Voltage (Vi)	0V to Vcc
Output Voltage (Vo)	0V to Vcc
Operating Temperature (Ta)	-55 C to +125 C
Minimum Input Edge Rate (Delta V/Delta T)	
ACTQ Devices	
Vin from 0.8V to 2.0V	
Vcc @ 4.5V 5.5V	125 mV/ns
Maximum High Level Output Current (Ioh)	-24 mA
Maximum Low Level Output Current (Iol)	+24 mA

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp. Range: -55C to 125C.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	High Level input Current	VCC=5.5V, VIH=5.5V	1, 2	INPUT		0.1	uA	1
			1, 2	INPUT		1.0	uA	2, 3
IIL	Low Level input Current	VCC=5.5V, VIL=0.0V	1, 2	INPUT		-0.1	uA	1
			1, 2	INPUT		-1.0	uA	2, 3
VOL	Low level output voltage	VCC=4.5V, VIH=2.0V, VIL=0.8V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
		VCC=4.5V, VIH=2.0V, VIL=0.8V, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
VIOL	Dynamic Output Current LOW	VCC=5.5V, VIH=5.5V, VIL=0.0V, IOL=50.0mA	1, 2, 5	OUTPUT		1.65	V	1, 2, 3
VOH	High Level Output Voltage	VCC=4.5V, VIH=2.0V, VIL=0.8V, IOH=-50.0uA	1, 2	OUTPUT	4.40		V	1, 2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOH=-50.0uA	1, 2	OUTPUT	5.40		V	1, 2, 3
		VCC=4.5V, VIH=2.0V, VIL=0.8V, IOH=-24.0mA	1, 2	OUTPUT	3.86		V	1
			1, 2	OUTPUT	3.70		V	2, 3
		VCC=5.5V, VIH=2.0V, VIL=0.8V, IOH=-24.0mA	1, 2	OUTPUT	4.86		V	1
			1, 2	OUTPUT	4.70		V	2, 3
VIOH	Dynamic Output Current High	VCC=5.5V, VIH=5.5V, VIL=0.0V, IOH=-50.0mA	1, 2, 5	OUTPUT	3.85		V	1, 2, 3
ICCH	Supply Current	VCC=5.5V, VIH=5.5V	1, 2	VCC		100	nA	1
			1, 2	VCC		40	uA	2, 3
ICCL	Supply Current	VCC=5.5V, VIH=0.0V	1, 2	VCC		100	nA	1
			1, 2	VCC		40	uA	2, 3
ICCF	Supply Current Functional	VCC=5.5V, VIH=0.0V	1, 2	VCC		100	nA	1
			1, 2	VCC		40	uA	2, 3
ICCT	Supply Current	VCC=5.5V, VIH=3.4V	1, 2	VCC		1.0	mA	1
			1, 2	VCC		1.6	mA	2, 3
VIKL		VCC=4.5V, IKL=-18mA	1, 2	INPUT		-1.2	V	1, 2, 3

Electrical Characteristics

DC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp. Range: -55C to 125C.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
VIKH		VCC=4.5V, IKH=18mA	1, 2	INPUT		5.7	V	1, 2, 3
VILD	Maximum Low Level Dynamic Input Voltage	VCC=5.0V, LOAD 50pF / 500 OHMS	6, 9	INPUT		0.8	V	4
VIHD	Minimum High Level Dynamic Input Voltage	VCC=5.0V, LOAD 50pF / 500 OHMS	6, 9	INPUT	2.2		V	4
VOLP	Quiet Output Maximum Dynamic VOL	VCC=5.0V, LOAD 50pF / 500 OHMS	6, 8	OUTPUT		1.5	V	4
VOLV	Quiet Output Minimum Dynamic VOL	VCC=5.0V, LOAD 50pF / 500 OHMS	6, 8	OUTPUT		-1.2	V	4

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
AC: CL=50pF, RL=500 OHMS, TR=3.0ns & TF=3.0ns, Temp Range: -55C to +125C.

tpLH	Propagation Delay	VCC=4.5V	3, 4, 7	An/Bn to On	1.5	7.0	ns	9
			3, 4, 7	An/Bn to On	1.5	7.5	ns	10, 11
tpHL	Propagation Delay	VCC=4.5V	3, 4, 7	An/Bn to On	1.5	7.0	ns	9
			3, 4, 7	An/Bn to On	1.5	7.5	ns	10, 11
tOSLH	Output to Output Skew	VCC=4.5V	6	On to On		1.0	ns	9, 10, 11
tOSHL	Output to Output Skew	VCC=4.5V	6	On to On		1.0	ns	9, 10, 11

- Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, & 8.
- Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C, +125C & -55C TEMPERATURE, SUBGROUPS A1, 2, 3, 7, & 8.
- Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY SUBGROUP A9.
- Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C, +125C & -55C TEMPERATURE, SUBGROUPS A9, 10 & 11.
- Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBANDED LIMITS SET FOR +25C, 2 MSEC DURATION MAX.
- Note 6: GUARANTEED BUT NOT TESTED. (DESIGN CHARACTERIZATION DATA)
- Note 7: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MINIMUM LIMITS.
- Note 8: MAX NUMBER OF OUTPUTS DEFINED AS (N). DATA INPUTS ARE DRIVEN 0V TO 3V. ONE OUTPUT @ VOL.
- Note 9: MAX NUMBER OF DATA INPUTS (N) SWITCHING. (N-1) INPUTS SWITCHING 0V TO 3V. INPUT-UNDER-TEST SWITCHING 3V TO THRESHOLD (VILD), 0V TO THRESHOLD (VIHD), FREQ= 1 MHZ.

Revision History

Rev	ECN #	Rel Date	Originator	Changes
0A0	M0003503	08/25/99	Linda Collins	Initial MDS Release