



ESD Safe Adjustable TorqueControl Tools



Includes Certificate



285 ESD Safe TorqueVario-S, With Window Scale

EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy
Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when torque setting has been attained. With Certificate of accuracy.

Item	Range	↔		↺↻		↻
No.	Inch lbs.	Increments	mm	lbs.	pkg.	
285 22*	15 - 80 (in/oz)	2.5 Inch oz	122 - 127	.33	1	
285 24	5 - 10	.2 Inch lbs	122 - 127	.34	1	
285 26	7.5 - 20	.5 Inch lbs	126 - 131	.42	1	

* +/- 10% (This unit only)

Each TorqueVario handle has unique serial number and certificate of calibration



With Certificate of Calibration



285 91 Set 24 Pcs. ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	↺↻
285 91	lbs.
	1.31
Slotted: 1.5, 2.0, 3.0, 4.0mm	
Phillips: #00, #0, #1	
TORX®: T6, T7, T8, T9, T10, T15	
Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"	
28524 Handle ESD Safe Range 5 - 10 Inch lbs.	

285 92 Set 24 Pcs. ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	↺↻
285 92	lbs.
	1.31
Slotted: 1.5, 2.0, 3.0, 4.0mm	
Phillips: #00, #0, #1	
TORX®: T6, T7, T8, T9, T10, T15	
Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"	
28526 Handle ESD Safe Range 7.5 - 20 Inch lbs.	

See ESD Safe Tools
On Pages 127-139, 163-165



288 ESD Safe Slotted Interchangeable Blades For TorqueVario-S

Slotted tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item	⊖	⊖	↔	↺↻	Max. Torque	↻
No.	mm	Inch	mm	lbs.	Nm	pkg.
288 01	1.5	.059	175	.07	0.15	1
288 03	2.0	.078	175	.07	0.4	1
288 05	3.0	.118	175	.07	0.6	1
288 07	3.5	.139	175	.07	1.1	1
288 09	4.0	.157	175	.07	2.5	1



288 ESD Safe Phillips Interchangeable Blades For TorqueVario-S

Phillips tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item	⊕	↔	⬢	↺↻	Max. Torque	↻
No.	Size	mm	mm	lbs.	Nm	pkg.
288 10	000	175	4.0	.07	0.4	1
288 12	00	175	4.0	.07	0.4	1
288 14	0	175	4.0	.07	0.9	1
288 16	1	175	4.0	.07	3.8	1



288 ESD Safe TORX® Interchangeable Blades For TorqueVario-S

TORX® tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, hard chromed.

Item	⊗	↔	⬢	↺↻	Max. Torque	↻
No.	Size	mm	mm	lbs.	Nm	pkg.
288 25	T5	175	4.0	.07	0.4	1
288 26	T6	175	4.0	.07	0.6	1
288 27	T7	175	4.0	.07	0.9	1
288 28	T8	175	4.0	.07	1.3	1
288 29	T9	175	4.0	.07	2.5	1
288 30	T10	175	4.0	.07	3.8	1



With Certificate of Calibration +/- 10%



288 90 Set 24 Piece TorqueVario-S ESD Safe Micro-Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool. Packed in a compact durable storage box.

Item No.	↺↻
288 90	lbs.
	1.33
Slotted: 1.5, 2.0, 3.0, 4.0mm	
Phillips: #00, #0, #1	
TORX®: T6, T7, T8, T9, T10, T15	
Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"	
28522 ESD Safe Handle Range 15-80 Inch/oz.	