


3 METERS LENGTH



Connector A
132453
SMA Jack Straight
Bulkhead - Rear Mount Brass Gold + Heatshrink




Connector B
132452
SMA Plug Right Angle
Brass Gold + Heatshrink

50 Ohm LMR-240
Continuity/Hi-Pot

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.



Connector A		Cable		Connector B	
Part #:	132453	Part #:	LMR-240	Part #:	132452
Description:	SMA BHD JK LMR240 Optimized 500	Description:	LMR-240 - FEP 0.24	Description:	SMA R/A PLUG LMR240 Optimized 500
Type:	SMA	Dielectric:	FEP	Type:	SMA
Gender:	Jack	Shielding:	Braid	Gender:	Plug
Body Type:	Straight	Diameter:	0.24	Body Type:	Right Angle
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder
Polarity:	Standard	Sheathing:	None	Polarity:	Standard
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Bulkhead - Rear Mount	Length:	3 Meters	Mounting:	Cable
Body Material:	Brass			Body Material:	Brass
Body Finish:	Gold			Body Finish:	Gold
IP Rating:	None			IP Rating:	None
Contact Material:	Beryllium Copper			Contact Material:	Brass
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	6 GHz			Max. Freq.:	6 GHz
Booting:	SMA Jack Straight BHD			Booting:	SMA Plug Right Angle
				Clocking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-ST-JK/SMA-RA-PL LMR24 3M

Part No:
Q-32039000M003M

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES