

TAPE Dispensers

Electronic

Additional info for
zcM1000 Modifications
 Can be found on Page 3 or at
www.STARTinternational.com/zcM1000

zcM1000B



For Narrow Tapes

- Special advancement roller for extra narrow tapes (1/8" (3mm) or thin tapes)
- Accepts tape widths from .125" to 1" (3 to 25mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

zcM1000C



For Glass Cloth Tapes

- Modified cutting head for flimsy and glass cloth tapes
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

zcM1000D



For Extra Short (5mm) Pieces of Tape

- Modified circuit board for minimum length setting of .2" (5mm)
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .2" to 39" (5 to 999mm)
- Photosensor unable to detect 5mm pieces. Suggested to use tweezers.

zcM1000E



For Dispensing Two Rolls of Tape

- Modified cutting head with dual photo sensors for dispensing two rolls of tape
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

zcM1000K



With Creaser

- Minimum length setting of .2" (5mm)
- Accepts tape widths from .5" to 1.1" (12 to 28mm)
- Photosensor unable to detect 5mm pieces. Tweezers are suggested for tape removal.

zcM1000T



For Thin Tapes

- Special advancement system to help dispense thin tapes
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

zcM1000NM



For Protective Film

- Modified zcM1000 with special non-marking advancement rollers for protective films
- Program a defined length and automatically advance and cut tape
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

zcM1000NS



For Double-Sided and VHB Tapes

- Special advancement roller for double-sided and VHB tapes
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)



Accessory Options

See page 30 or visit
www.STARTinternational.com/zcMAccessories

For 230V machines,
 please add "-2" to the
 end of the model number.
 (Example: zcM1000-2)

MODEL #	Tape Width	Cut Length	Max. Outside Dia. of Roll	3-in-1 Core Holder	Accuracy of Cut**	Length Setting	Weight	Dimensions
zcM1000	.28 to 2" (7 to 51mm)	.79 to 39" (20 to 999mm)	7" (178mm)	1", 1.4", 3" (25, 35, 76mm)	+/- .04" (1mm)	digital (LED)	5.3 lbs (3.4 kg)	9.7"(L) x 5.4"(W) x 5.9"(H) 24.5cm(L) x 13.7cm(W) x 15cm(H)

Electrical requirements: 117V 50/60Hz, <1 amp (230V 50/60Hz CE available) ** dependent on material