


Multi-Stud Ring Tongues – Nylon Insulated with Insulation Grip




Product Number [†]	UPC (054007-)	Wire Range (AWG)	Stud Size	Wire					Barrel Length	Barrel I.D.	Maximum Insulation Diameter	Terminals per:	
				W	C	L	E	Thickness				Carton	Case
MNG18-610RX	49611	22-18	6/8/10	0.34	0.31	1.00	0.75	0.030	0.25	0.070	0.145	100	500
MNG18-610RK	01344	22-18	6/8/10	0.34	0.31	1.00	0.75	0.030	0.25	0.070	0.145	—	1000
MNG14-610RX	49636	16-14	6/8/10	0.34	0.31	1.02	0.77	0.030	0.25	0.090	0.170	100	500
MNG14-610RK	01853	16-14	6/8/10	0.34	0.31	1.02	0.77	0.030	0.25	0.090	0.170	—	1000
MNG10-610RX	49646	12-10	6/8/10	0.39	0.35	1.19	0.80	0.040	0.25	0.135	0.250	50	100
MNG10-610RK	02100	12-10	6/8/10	0.39	0.35	1.19	0.80	0.040	0.25	0.135	0.250	—	500



MNG18-610R

Stud Size
6/8/10


Wire Range
22-18



MNG14-610R

Stud Size
6/8/10

Wire Range
16-14



MNG10-610R

Stud Size
6/8/10

Wire Range
12-10

Stud Size
Wire Range