

# DDR4 SDRAM SODIMM

## Addendum

### MTA9ASF1G72HBZ – 8GB


#### Introduction

Information provided here is in addition to or supersedes information provided in the Micron DDR4 SODIMM Core data sheet.

#### Features

- DDR4 functionality and operations supported as defined in the component data sheet
- Features and specifications supported in the Micron DDR4 SODIMM Core data sheet
- 260-pin, small-outline dual in-line memory module (SODIMM)
- Fast data transfer rate: PC4-3200
- 8GB (1 Gig x 72)
- Data bus inversion (DBI) for data bus
- Supports ECC error detection and correction
- Single-rank
- On-board I<sup>2</sup>C temperature sensor with integrated serial presence-detect (SPD) EEPROM
- 16 internal banks; 4 groups of 4 banks each

**Figure 1: 260-Pin SODIMM**



#### Options

- Operating temperature
  - Extended ( $-40^{\circ}\text{C} \leq T_{\text{OPER}} \leq 105^{\circ}\text{C}$ )
- Package
  - 260-pin DIMM (Green)
- Frequency/CAS latency
  - 0.625ns @ CL = 22 (DDR4-3200)

#### Marking

B  
Z  
-3G2

**Table 1: Addressing**

Parameter	8GB
Row address	64K A[15:0]
Column address	1K A[9:0]
Device bank group address	4 BG[1:0]
Device bank address per group	4 BA[1:0]
Device configuration	8Gb (1 Gig x 8), 16 banks
Module rank address	CS0_n



**Table 2: Part Numbers and Timing Parameters – 8GB Modules**

Base device: MT40A1G8,<sup>1</sup> 8Gb DDR4 SDRAM

Part Number <sup>2</sup>	Module Density	Configuration	Module Bandwidth	Memory Clock/ Data Rate	Clock Cycles (CL-nRCD-nRP)
MTA9ASF1G72HBZ-3G2__	8GB	1 Gig x 72	25.6 GB/s	0.625ns/3200 MT/s	22-22-22

- Notes:
1. The data sheet for the base device can be found at [micron.com](http://micron.com).
  2. All part numbers end with a two-place code (not shown) that designates component and PCB revisions. Consult factory for current revision codes. Example: MTA9ASF1G72HBZ-3G2E1.

## Important Notes and Warnings

Micron Technology, Inc. ("Micron") reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions. This document supersedes and replaces all information supplied prior to the publication hereof. You may not rely on any information set forth in this document if you obtain the product described herein from any unauthorized distributor or other source not authorized by Micron.

**Automotive Applications.** Products are not designed or intended for use in automotive applications unless specifically designated by Micron as automotive-grade by their respective data sheets. Distributor and customer/distributor shall assume the sole risk and liability for and shall indemnify and hold Micron harmless against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, death, or property damage resulting directly or indirectly from any use of non-automotive-grade products in automotive applications. Customer/distributor shall ensure that the terms and conditions of sale between customer/distributor and any customer of distributor/customer (1) state that Micron products are not designed or intended for use in automotive applications unless specifically designated by Micron as automotive-grade by their respective data sheets and (2) require such customer of distributor/customer to indemnify and hold Micron harmless against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, death, or property damage resulting from any use of non-automotive-grade products in automotive applications.

**Critical Applications.** Products are not authorized for use in applications in which failure of the Micron component could result, directly or indirectly in death, personal injury, or severe property or environmental damage ("Critical Applications"). Customer must protect against death, personal injury, and severe property and environmental damage by incorporating safety design measures into customer's applications to ensure that failure of the Micron component will not result in such harms. Should customer or distributor purchase, use, or sell any Micron component for any critical application, customer and distributor shall indemnify and hold harmless Micron and its subsidiaries, subcontractors, and affiliates and the directors, officers, and employees of each against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, or death arising in any way out of such critical application, whether or not Micron or its subsidiaries, subcontractors, or affiliates were negligent in the design, manufacture, or warning of the Micron product.

**Customer Responsibility.** Customers are responsible for the design, manufacture, and operation of their systems, applications, and products using Micron products. ALL SEMICONDUCTOR PRODUCTS HAVE INHERENT FAILURE RATES AND LIMITED USEFUL LIVES. IT IS THE CUSTOMER'S SOLE RESPONSIBILITY TO DETERMINE WHETHER THE MICRON PRODUCT IS SUITABLE AND FIT FOR THE CUSTOMER'S SYSTEM, APPLICATION, OR PRODUCT. Customers must ensure that adequate design, manufacturing, and operating safeguards are included in customer's applications and products to eliminate the risk that personal injury, death, or severe property or environmental damages will result from failure of any semiconductor component.

**Limited Warranty.** In no event shall Micron be liable for any indirect, incidental, punitive, special or consequential damages (including without limitation lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort, warranty, breach of contract or other legal theory, unless explicitly stated in a written agreement executed by Micron's duly authorized representative.



## DQ Map

**Table 3: Component-to-Module DQ Map (PCB 2450, 2974, 3219, 3239)**

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U2	0	3	21	U3	0	19	63
	1	0	8		1	17	49
	2	2	20		2	18	62
	3	1	7		3	16	50
	4	6	16		4	22	58
	5	4	4		5	21	45
	6	7	17		6	23	59
	7	5	3		7	20	46
U4	0	CB7	104	U5	0	38	183
	1	CB4	88		1	36	170
	2	CB6	100		2	39	182
	3	CB5	87		3	37	169
	4	CB3	105		4	35	186
	5	CB1	91		5	32	174
	6	CB2	104		6	34	187
	7	CB0	92		7	33	173
U6	0	55	225	U7	0	56	237
	1	52	211		1	58	249
	2	54	224		2	57	236
	3	53	212		3	59	250
	4	50	228		4	61	233
	5	49	215		5	62	245
	6	51	229		6	60	232
	7	48	216		7	63	246
U8	0	40	195	U9	0	29	67
	1	42	207		1	30	79
	2	41	194		2	28	66
	3	43	208		3	31	80
	4	44	191		4	24	70
	5	47	204		5	26	83
	6	45	190		6	25	71
	7	46	203		7	27	84



**Table 3: Component-to-Module DQ Map (PCB 2450, 2974, 3219, 3239) (Continued)**

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U10	0	12	24				
	1	15	37				
	2	13	25				
	3	14	38				
	4	9	29				
	5	10	41				
	6	8	28				
	7	11	42				



## I<sub>DD</sub> Specifications


**Table 4: DDR4 I<sub>DD</sub> Specifications and Conditions – 8GB (Die Revision E)**

Values are for the MT40A1G8 DDR4 SDRAM only and are computed from values specified in the 8Gb (1 Gig x 8) component data sheet

Parameter	Symbol	3200	Units
One bank ACTIVATE-PRECHARGE current	I <sub>DD0</sub>	459	mA
One bank ACTIVATE-PRECHARGE, wordline boost, I <sub>pp</sub> current	I <sub>PP0</sub>	27	mA
One bank ACTIVATE-READ-PRECHARGE current	I <sub>DD1</sub>	603	mA
Precharge standby current	I <sub>DD2N</sub>	324	mA
Precharge standby ODT current	I <sub>DD2NT</sub>	432	mA
Precharge power-down current	I <sub>DD2P</sub>	234	mA
Precharge quiet standby current	I <sub>DD2Q</sub>	261	mA
Active standby current	I <sub>DD3N</sub>	423	mA
Active standby I <sub>pp</sub> current	I <sub>PP3N</sub>	27	mA
Active power-down current	I <sub>DD3P</sub>	333	mA
Burst read current	I <sub>DD4R</sub>	1701	mA
Burst write current	I <sub>DD4W</sub>	1440	mA
Burst refresh current (1x REF)	I <sub>DD5R</sub>	900	mA
Burst refresh I <sub>pp</sub> current (1x REF)	I <sub>PP5R</sub>	45	mA
Self refresh current: Normal temperature range (0°C to 85°C)	I <sub>DD6N</sub> (0–85°C)	306	mA
Self refresh current: Extended temperature range (0°C to 95°C)	I <sub>DD6E</sub> (0–95°C)	855	mA
Self refresh current: Reduced temperature range (0°C to 45°C)	I <sub>DD6R</sub> (0–45°C)	189	mA
Auto self refresh current (25°C)	I <sub>DD6A</sub> (25°C)	78	mA
Auto self refresh current (45°C)	I <sub>DD6A</sub> (45°C)	189	mA
Auto self refresh current (75°C)	I <sub>DD6A</sub> (75°C)	279	mA
Auto self refresh current (95°C)	I <sub>DD6A</sub> (95°C)	855	mA
Auto self refresh I <sub>pp</sub> current	I <sub>PP6X</sub>	54	mA
Bank interleave read current	I <sub>DD7</sub>	1755	mA
Bank interleave read I <sub>pp</sub> current	I <sub>PP7</sub>	117	mA
Maximum power-down current	I <sub>DD8</sub>	180	mA

## Functional Block Diagram


Figure 2: Functional Block Diagram



Note: 1. The ZQ ball on each DDR4 component is connected to an external 240Ω ±1% resistor that is tied to ground. It is used for the calibration of the component's ODT and output driver.

## Module Dimensions


**Figure 3: 260 Pin DDR4 SODIMM - PCB 2974**



- Notes:
1. All dimensions are in millimeters; MAX/MIN or typical (TYP) where noted.
  2. Tolerance on all dimensions  $\pm 0.15$ mm unless otherwise specified.
  3. The dimensional diagram is for reference only.



**Figure 4: 260 Pin DDR4 SODIMM - PCB 3219**



- Notes:
1. All dimensions are in millimeters; MAX/MIN or typical (TYP) where noted.
  2. Tolerance on all dimensions  $\pm 0.15$ mm unless otherwise specified.
  3. The dimensional diagram is for reference only.

8000 S. Federal Way, P.O. Box 6, Boise, ID 83707-0006, Tel: 208-368-4000  
[www.micron.com/products/support](http://www.micron.com/products/support) Sales inquiries: 800-932-4992  
 Micron and the Micron logo are trademarks of Micron Technology, Inc.  
 All other trademarks are the property of their respective owners.

This data sheet contains minimum and maximum limits specified over the power supply and temperature range set forth herein. Although considered final, these specifications are subject to change, as further product development and data characterization sometimes occur.